




RIME PENDANT LAMP - EU VERSION


TAF STUDIO ON THE DESIGN "Designing simple things is often one of the hardest things to do. We wanted to create a simple lamp with a glass shape, giving it a soft expression while making its top and pendant tube as subtle as possible. We were inspired by the shape of acorns for the gentle lines of the pendant while hinting towards the shaded expression of ice and rime for the glass of the design, allowing for the light to shine slightly through with a refined touch. The Rime Pendant Lamp brings a timeless yet modern perspective to the archetypal light through its translucent shade and graphic form."







READY-TO-SHIP OPTIONS



DESIGNED BY / YEAR OF DESIGN

TAF Studio / 2020

ABOUT THE DESIGNER

TAF Studio is a Stockholm-based design and architecture studio, founded by Gabriella Gustafson and Mattias Ståhlbom. The duo works within product and interior design.

CATEGORY

Pendant lamp

ENVIRONMENT

Indoor

COUNTRY OF PRODUCTION

Poland

DESCRIPTION

Bringing a new perspective to the glass pendant lamp through its mouthblown, translucent glass that has been sandblasted for a refined surface expression. Designed with a characteristic form, complemented by a powder-coated top-part, pendant tube and cord in a matching color for a subtle touch.

MATERIAL

Mouthblown glass shade. Aluminum, powder coated top-piece and pendant tube. PVC cord.

CORD LENGTH

400 cm / 13'1"

BULB INCLUDED

Ø12: Yes Ø25, Ø37, Ø45: No

CEILING CAP INCLUDED

Yes - white ØI2 & Ø25: Ø 9 cm / 3.5" H 5,6 cm / 2.2" Ø37 & Ø45: Ø II cm / 4.3" H 3,5 cm / I.4"

DIMMABLE FUNCTION

Yes, if dimmable bulb is used.

CLEANING AND CARE

Clean with a moist cloth. If necessary use a little dish soap on the cloth.



RIME PENDANT LAMP - EU VERSION











Frequency

LAMP RATING Ø12

Voltage 220 - 240V 50/60Hz IP Rating IP2O Classification Class II Socket IxG9 Max. 25W

CRI 90 Dimmable Yes Risk Group Except

Lamp base

Dimensions

ltem

Watt

Lumen


Kelvin


BULB SPECIFICATION Ø12

Lumen Maintenance 20.000h

BULB RECOMMENDATION Ø25

Light source shape P45





LAMP RATING Ø25

220 - 240V Voltage 50/60Hz Frequency IP Rating IP2O Classification Class II Socket 1 x FI4 Max. 40W

LAMP RATING Ø37

220 - 240V Voltage Frequency 50/60Hz IP Rating IP2O Classification Class I Socket 1 x E27

Recommended

400-800 lm (6-IO W LED) light output LED with opal or frosted Light source type

F14

Ø45 X 80 mm

G9 LED

190 lm/W 2700K

3 W

diffuser

Max. 60W

BULB RECOMMENDATION Ø37 Lamp base E27

Dimensions Ø60 X IIO mm Light source shape A6O

Recommended

750-I500 lm (8-I2 W LED) light output LED with opal or frosted Light source type

diffuser

LAMP RATING Ø45

Voltage 220 - 240V Frequency 50/60Hz **IP** Rating IP9O Classification Class I 1 x E27 Socket Max. 60W

BULB RECOMMENDATION Ø45

Lamp base Dimensions Ø77 X I45 mm Light source shape A67

Recommended

750-I500 lm (8-I2 W LED) light output Light source type LED with opal or frosted

diffuser

GENERAL STANDARDS & CERTIFICATES

EU/UK AUS/NZL

REACH

874/2012

Directive - EC/I9O7/2OO6

RCM. EN 60598-I and EN 60598-2-I (AUZ/NZ deviations)

ROHS Directive - 2011/65/EU amended RoHS 3 Directive 2015/863 ECO Design Directive - 245/2009/EC

WEEE Directive - 2012/19/EU