



**PLBEL090**  
Design by Manuel Vivian

Collection consisting of suspended and ceiling lamps with a metal frame covered with strips of extra smooth flame-retardant pongé fabric. Available in several colours and sizes.

Typology: CEILING

**Ratings**


- E27
- Downlight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off
- Steel frame
- Light covering in jersey

Product code composition

**BELL** / diffuser *INCLUDED, with upward and downward lighting*

| Type | Article     | Colours                 | Finish    | Source   |
|------|-------------|-------------------------|-----------|--|
| PL   | BEL 090 E27 | <b>BC</b> white         | <b>XX</b> | <b>E27</b> 3 x Max 16W LED or<br>3 x Max 23W fluo or<br>3 x Max 57W halo |
|      |             | <b>BL</b> electric blue |           |  |
|      |             | <b>BW</b> warm white    |           |  |
|      |             | <b>GI</b> gold yellow   |           |  |
|      |             | <b>MA</b> brown         |           |  |
|      |             | <b>MT</b> brick red     |           |  |
|      |             | <b>NE</b> black         |           |  |
|      |             | <b>RB</b> burgundy      |           |  |
|      |             | <b>RS</b> red           |           |  |
|      |             | <b>VE</b> green         |           |  |

kg 8 m<sup>3</sup> 0.98



CE IP20 **+LED**

example composition code | PL | BEL090E27 | GI | XX

Available colors



EELc (Energy Efficiency Label compatibility): E, D, C, B, A, A+

SPBEL090E27\_XX      CUSTOMER \_\_\_\_\_      NOTES \_\_\_\_\_

**NOTICE:**  
Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources.  
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.