## **Product data sheet**

**Q**UASAR


Date: November 11th 2021




## **ABOUT POLLUX SUSPENSION**

## by Jan Pauwels

Pollux looks structured but still harmonious. Modular placed LED circuit boards and tiny metal rods are the only two basic elements of this light fixture. They give the lamp its structure and shape. The shape is totally irregular and asymmetrical. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards.





DIMENICIONIC

L 205 cm80.7 inch H 187 cm 73.6 inch W 105 cm 41.3 inch

CANOPY

CABLELENGTH
Up to 0 cm 0 inch

IGHTSOURCE

886 x led 12V/0,6W, 2800K, 26580LM

INCLUDED

Yes



FINISH TYPE.NR

Nickel
Brass
Copper
Blackbrass

W

TYPE suspension

**STANDARD** 

Н

OPTIONAL 2400K.

TRANSFORMER/DRIVER Meanwell HLG600

DIMMING 0-10V

CLASSIFICATION UL no

IP20 yes

## Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands T. +31-(0)183-447887 F. +31-(0)183-448337 export@quasar.nl www.quasar.nl