




BLIEK ROUND

CEILING RECESSED



available from summer 2020



1.0 LED

LED 7/10W | 350/500mA | 18V
COB 3-step | excl. power supply
aluminium powder coated

0.45kg IP20 36°

126-130 60° 355° 75 4-30

| | CODE |
|--|---------|
| | 125161W |
| | 125161B |
| | 125161K |


| LIGHT COLOUR | LUMEN | CRI | CODE |
|------------------|---------|-----|------|
| 2700K | 540/740 | >90 | 3 |
| 3000K | 490/790 | >90 | 5 |
| 4000K | 630/840 | >90 | 6 |
| 1800-2850K 16V | 300/410 | >95 | 9 |

ALWAYS USE

power supply | 500mA

| | CODE |
|----------|----------|
| 10W | 90214405 |
| 15W dim | 90224501 |
| 20W DALI | 90244602 |

more power supplies on page 695



1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.42kg IP20 36°

127 60° 350° 75 4-30

| | CODE |
|--|----------|
| | 125120W0 |
| | 125120B0 |
| | 125120K0 |

ALWAYS USE

PAR16 LED GU10 7W | phase-cut dim

| | CODE |
|------------|----------|
| 2700K | 901228W2 |
| 3000K | 901228W4 |
| 1800-2850K | 901229S9 |

more lamps and specs on page 701