





# BLIEK SQUARE

CEILING RECESSED



## 1.0 LED

LED 7/10W | 350/500mA | 18V  
COB 3-step | excl. power supply  
aluminium powder coated

0.47kg | IP20 | 36°

111x111 | 60° | 355 | 75 | 4-30

|       | CODE     |
|-------|----------|
| White | 125261W_ |
| Black | 125261B_ |

| LIGHT COLOUR | LUMEN       | CRI | CODE |
|--------------|-------------|-----|------|
| 2700K        | 540/740     | >90 | 3    |
| 3000K        | 490/790     | >90 | 5    |
| 4000K        | 630/840     | >90 | 6    |
| 1800-2850K   | 16V 300/410 | >95 | 9    |

## ALWAYS USE

power supply | 500mA

|          | CODE     |
|----------|----------|
| 10W      | 90214405 |
| 15W dim  | 90224501 |
| 20W DALI | 90244602 |

more power supplies on page 695

## 1.0 PAR16

PAR16 max. 12W | GU10  
100-240VAC | 50-60Hz  
aluminium powder coated

0.45kg | IP20 | 36°

111x111 | 60° | 355 | 75 | 4-30

|       | CODE     |
|-------|----------|
| White | 125220W0 |
| Black | 125220B0 |

## OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

|            | CODE     |
|------------|----------|
| 2700K      | 901228W2 |
| 3000K      | 901228W4 |
| 1800-2850K | 901229S9 |

more lamps and specs on page 701

available from summer 2020