






# kreon specification sheet

<b>your selection</b>	KR907033-9027-SP   aplis in-line 40 downlight, LED
KR707701	plasterkits   plasterkit for concrete installation, deep recessed, no shadowgap
<b>product</b>	KR907033-9027-SP   aplis in-line 40 downlight, LED
<b>general information</b>	
application	recessed luminaire for ceilings
direction of mounting	↓
protection class	3
ip classification	40
power	2W
electric gear	not included
<b>visible dimensions</b>	
diameter	40mm
<b>illuminant</b>	
output	138lm / 172lm
CCT	2700K
CRI	90+
drive current	700mA / 1050mA
lamptype	LED
symbol	
wattage	2W / 3,2W
beam angle	spot (10°)



**kreon nv**  
 Industrieweg Noord 1152  
 3660 Oudsbergen  
 Belgium  
 T +32 89 81 97 80  
 F +32 89 81 97 90  
 M mailbox@kreon.com  
 www.kreon.com

It is possible that the  
 product images do not  
 match the selected  
 configuration

<b>material and surface</b>	
socket holder	
material	aluminium, die-cast
surface treatment	cataphoretically painted
movement mechanism	
material	aluminium, die-cast
surface treatment	cataphoretically painted
<b>cut-out dimensions</b>	

# kreon specification sheet

in plasterboard	
depth	80mm
diameter	63mm
panel	9-14mm

required accessories	
plasterkits	KR707701   plasterkit for concrete installation, deep recessed, no shadowgap