





kreon specification sheet

your selection	KR907033-9027-SP down in-line 40 downlight, LED
KR707114	plasterkits plasterkit for Down in-Line 40
KR707111	plasterkits plasterkit concrete for down in-line 40
KR707714	plasterkits plasterkit, deep recessed, no shadowgap
KR707711	plasterkits plasterkit for concrete installation, deep recessed, no shadowgap

product	KR907033-9027-SP down in-line 40 downlight, LED
----------------	---

general information	
application	recessed luminaire for ceilings
direction of mounting	↓
protection class	3
ip classification	40
certification	CE
power	2W
electric gear	not included
visible dimensions	
LxW	40mm x 40mm
illuminant	
output	138lm / 172lm
CCT	2700K
CRI	90+
drive current	700mA / 1050mA
lamptype	LED
symbol	
wattage	2W / 3,2W
beam angle	spot (10°)



kreon nv
 Industrieweg Noord 1152
 3660 Oudsbergen
 Belgium
 T +32 89 81 97 80
 F +32 89 81 97 90
 M mailbox@kreon.com
 www.kreon.com

It is possible that the product images do not match the selected configuration

material and surface	
louvre	
material	zamak, die cast
surface treatment	powdercoated
installation frame	
material	aluminium, die-cast
surface treatment	powdercoated
cut-out dimensions	
in plasterboard	
LxWxD	63mm x 63mm x 80mm
panel	9-14mm

kreon specification sheet

required accessories	
plasterkits	KR707114 plasterkit for Down in-Line 40
full dimensions	
height	22,1mm
diameter	74,2mm
material and surface	
material	plastics (PA 6.6)
cut-out dimensions	
in plasterboard	
LxW	63 mm x 63 mm
panel	9-14
plasterkits KR707111 plasterkit concrete for down in-line 40	
plasterkits KR707714 plasterkit, deep recessed, no shadowgap	
plasterkits KR707711 plasterkit for concrete installation, deep recessed, no shadowgap	

