



kreon specification sheet

your selection	KR915341-9027-DD dolma 40 up/down light, LED, white
KR745002	tracks and profiles dolma 40 profile, recessed, black anodised
product	KR915341-9027-DD dolma 40 up/down light, LED, white
general information	
application	recessed profile for walls
direction of mounting	↕↔
ip classification	20
input voltage	230V
power	3,2W
electric gear	included
dimming	DALI
full dimensions	
LxW	150mm x 50mm
illuminant	
output	111lm
CCT	2700K
CRI	90+
drive current	1050mA
lamptype	LED
symbol	
wattage	3,2W
voltage	230V (gear incl.) / 3V (gear excl.)



kreon nv
 Industrieweg Noord 1152
 3660 Oudsbergen
 Belgium
 T +32 89 81 97 80
 F +32 89 81 97 80
 M mailbox@kreon.com
 www.kreon.com

It is possible that the
 product images do not
 match the selected
 configuration

kreon specification sheet

required accessories	
tracks and profiles	KR745002 dolma 40 profile, recessed, black anodised
general information	
application	recessed profile for walls
protection class	1
full dimensions	
LxW	max. 6000mm x 100mm
visible dimensions	
LxW	max. 6000mm x 65mm
material and surface	
profile	
material	aluminium, extruded
surface treatment	anodised
colour	black
cut-out dimensions	
in plasterboard	
depth	80mm
panel	12,5mm
remarks	<p>The profile can be incorporated into plasterboard and finished with polyester gypsum or can be used in combination with other dry building materials.</p> <p>The profile is supplied preassembled and pre-wired, including all luminaires and gear. Subsequently the position of the single luminaires in the profile can not be changed.</p> <p>Max. length of a single run profile = 6000mm. Shipping length depends on transport possibilities.</p>

