



kreon specification sheet

your selection	KR915443-8027-SW dolma 80 up & downlight, LED, grey
KR715002	tracks and profiles Dolma 80 profile, recessed, black anodised
product	KR915443-8027-SW dolma 80 up & downlight, LED, grey
general information	
application	luminaire for recessed profile in ceilings and walls
direction of mounting	↕↕
protection class	1
ip classification	20
certification	CE
input voltage	230V
electric gear	included
dimming	ON-OFF
visible dimensions	
LxW	245mm x 80 mm
full dimensions	
LxWxD	245mm x 80mm x 60mm
illuminant	
output	126lm
CCT	2700K
CRI	80+
lamptype	LED
symbol	
wattage	8,4W
voltage	230V
material and surface	
housing	
material	sheet steel, galvanised
colour	grey
surface treatment	powdercoated
glass cover	
inclosed	glass, frosted



kreon nv
 Industrieweg Noord 1152
 3660 Oudsbergen
 Belgium
 T +32 89 81 97 80
 F +32 89 81 97 90
 M mailbox@kreon.com
 www.kreon.com


It is possible that the
 product images do not
 match the selected
 configuration

kreon specification sheet

Installation requires the Dolma profile. Please refer to the description of the profile for cut-out dimensions and panel thickness.

The luminaire can only be used in a Dolma 80 profile.

The profile is supplied pre-assembled, including luminaires and gear. The length and the combination of luminaires required must be specified on a separate order form.



required accessories	
tracks and profiles	KR715002 Dolma 80 profile, recessed, black anodised
general information	
application	recessed profile for walls
protection class	1
ip classification	40
certification	CE, ENEC
full dimensions	
LxWxH	max. 6000mm x 185mm x 70mm
visible dimensions	
LxW	max. 6000mm x 80mm
material and surface	
profile	
material	aluminium, extruded
surface treatment	anodised
colour	black
cut-out dimensions	
in plasterboard	
LxWxH	L+10 mm x 215 mm x 80 mm
remarks	<p>The profile can be incorporated into plasterboard and finished with polyester gypsum or can be used in combination with other dry building materials.</p> <p>The profile is supplied preassembled and pre-wired, including all luminaires and gear. Subsequently the position of the single luminaires in the profile can not be changed.</p> <p>Length and desired combination of luminaires must be specified on a separate order form. The profile can be supplied in any length up to 6000 mm.</p> <p>Due to the maximum size of available back plates, the distance between the single luminaires may not exceed 3000 mm.</p>