



kreon specification sheet

your selection	KR915471-8027-SW dolma 80 symmetrical light, LED, white
KR715002	tracks and profiles Dolma 80 profile, recessed, black anodised
product	KR915471-8027-SW dolma 80 symmetrical light, LED, white
general information	
application	luminaire for recessed profile in ceilings and walls
direction of mounting	↕↕
protection class	1
ip classification	20
certification	CE
input voltage	230V
power	8,4W
electric gear	included
dimming	ON-OFF
visible dimensions	
LxWxD	175mm x 80mm x 60mm
full dimensions	
LxW	175mm x 80mm
illuminant	
output	126lm
CCT	2700K
CRI	80+
lamptype	LED
symbol	
wattage	8,4W
voltage	230V
material and surface	
housing	
material	sheet steel
colour	white
surface treatment	powdercoated
glass cover	
inclosed	acrylic glass, frosted



kreon nv
 Industrieweg Noord 1152
 3660 Oudsbergen
 Belgium
 T +32 89 81 97 80
 F +32 89 81 97 90
 M mailbox@kreon.com
 www.kreon.com

It is possible that the product images do not match the selected configuration

kreon specification sheet

required accessories	
tracks and profiles	KR715002 Dolma 80 profile, recessed, black anodised
general information	
application	recessed profile for walls
protection class	1
ip classification	40
certification	CE, ENEC
full dimensions	
LxWxH	max. 6000mm x 185mm x 70mm
visible dimensions	
LxW	max. 6000mm x 80mm
material and surface	
profile	
material	aluminium, extruded
surface treatment	anodised
colour	black
cut-out dimensions	
in plasterboard	
LxWxH	L+10 mm x 215 mm x 80 mm
remarks	<p>The profile can be incorporated into plasterboard and finished with polyester gypsum or can be used in combination with other dry building materials.</p> <p>The profile is supplied preassembled and pre-wired, including all luminaires and gear. Subsequently the position of the single luminaires in the profile can not be changed.</p> <p>Length and desired combination of luminaires must be specified on a separate order form. The profile can be supplied in any length up to 6000 mm.</p> <p>Due to the maximum size of available back plates, the distance between the single luminaires may not exceed 3000 mm.</p>

