


# kreon specification sheet

<b>your selection</b>	KR934001-9027-FL-PD   halon 40 single in-cana, LED, white
KR755201	tracks and profiles   Cana 40 profile, white
KR755202	tracks and profiles   Cana 40 profile, black

<b>product</b>	KR934001-9027-FL-PD   halon 40 single in-cana, LED, white
----------------	---

<b>general information</b>	
application	luminaire for recessed or surface mounted profile
direction of mounting	↓→
protection class	3
ip classification	40
dimming	phase dimming
<b>visible dimensions</b>	
LxW	300mm x 50mm
minimum module spacing	100mm
<b>fixture dimensions</b>	
diameter	45mm



**kreon nv**  
 Industrierweg Noord 1152  
 3660 Oudsbergen  
 Belgium  
 T +32 89 81 97 80  
 F +32 89 81 97 90  
 M mailbox@kreon.com  
 www.kreon.com

It is possible that the  
 product images do not  
 match the selected  
 configuration

<b>illuminant</b>	
output	121lm
CCT	2700K
CRI	90+
drive current	700mA
lamptype	LED
symbol	
wattage	2W
rotation/inclination	360°/30°
beam angle	flood (24°)

# kreon specification sheet

Combinations can be specified on order form.


The coverplates on the inside of the profile are always black

The minimum module spacing is the minimum center distance to the next in-Cana 40 module.

Use constant current LED driver on remote. One circuit may not exceed a forward voltage of 55V to keep the profile class 3. Max. 2 circuits

LED drivers are integrated in the profile. Class 1 profile, input voltage is 230V. Max. 1 circuit. Cannot be combined with Ligna 40 in-Cana fixtures.

<b>required accessories</b>	
<b>tracks and profiles</b>	KR755201   Cana 40 profile, white
<b>general information</b>	
ip classification	40
input voltage	230V
<b>full dimensions</b>	
LxWxH	max. 6000mm x 54mm x 80mm
<b>material and surface</b>	
profile	
material	aluminium, extruded
colour	white / black
<b>cut-out dimensions</b>	
<b>in plasterboard</b>	
LxWxH	L x 75mm x 115mm
<b>remarks</b>	
The profile is supplied pre-assembled	
Max. length of a single run profile = 6000mm. Shipping length depends on transport possibilities.	



# kreon specification sheet

<b>tracks and profiles</b>	KR755202   Cana 40 profile, black
<b>general information</b>	
ip classification	40
input voltage	230V
<b>full dimensions</b>	
LxWxH	max. 6000mm x 54mm x 80mm
<b>material and surface</b>	
profile	
material	aluminium, extruded
colour	black / black
<b>cut-out dimensions</b>	
<b>in plasterboard</b>	
WxH	75mm x 115mm
pending height	2,5m
panel	max. 26mm
<b>remarks</b>	
	The profile is supplied pre-assembled
	Max. length of a single run profile = 6000mm. Shipping length depends on transport possibilities.

