


kreon specification sheet

your selection	KR934002-9027-SP-DD holon 40 single in-cana, LED, black
KR755201	tracks and profiles Cana 40 profile, white
product	KR934002-9027-SP-DD holon 40 single in-cana, LED, black
general information	
application	luminaire for recessed or surface mounted profile
direction of mounting	↓→
protection class	3
ip classification	40
dimming	DALI
visible dimensions	
LxW	300mm x 50mm
minimum module spacing	100mm
fixture dimensions	
diameter	45mm



kreon nv
 Industrieweg Noord 1152
 3660 Oudsbergen
 Belgium
 T +32 89 81 97 80
 F +32 89 81 97 90
 M mailbox@kreon.com
 www.kreon.com

It is possible that the product images do not match the selected configuration

illuminant	
output	121lm
CCT	2700K
CRI	90+
drive current	700mA
lamptype	LED
symbol	
wattage	2W
rotation/inclination	360°/30°
beam angle	spot (10°)

kreon specification sheet

Combinations can be specified on order form.

The coverplates on the inside of the profile are always black

The minimum module spacing is the minimum center distance to the next in-Cana 40 module.

Use constant current LED driver on remote. One circuit may not exceed a forward voltage of 55V to keep the profile class 3. Max. 2 circuits

LED drivers are integrated in the profile. Class 1 profile, input voltage is 230V. Max. 1 circuit. Cannot be combined with Ligna 40 in-Cana fixtures.

required accessories	
tracks and profiles	KR755201 Cana 40 profile, white
general information	
ip classification	40
input voltage	230V
dimming	DALI
full dimensions	
LxWxH	max. 6000mm x 54mm x 80mm
material and surface	
profile	
material	aluminium, extruded
colour	white / black
cut-out dimensions	
in plasterboard	
LxWxH	L x 75mm x 115mm
remarks	
The profile is supplied pre-assembled	
Max. length of a single run profile = 6000mm. Shipping length depends on transport possibilities.	

