



# kreon specification sheet

<b>your selection</b>	KR934511-9827-SP-DD   holon 80 twin in-cana, LED, white
KR775201	tracks and profiles   Cana 80 recessed mounted profile, white
KR775202	tracks and profiles   Cana 80 recessed mounted profile, black
KR705010	plasterkits   trimless plasterkit profile

<b>product</b>	KR934511-9827-SP-DD   holon 80 twin in-cana, LED, white
----------------	---

<b>general information</b>	
application	luminaire for recessed profile in ceilings
direction of mounting	↓→
protection class	1
ip classification	40
input voltage	230V
electric gear	included
dimming	DALI
<b>visible dimensions</b>	
LxW	550mm x 90mm
<b>fixture dimensions</b>	
LxW	85mm x 85mm (2x)



**kreon nv**  
 Industrierweg Noord 1152  
 3660 Oudsbergen  
 Belgium  
 T +32 89 81 97 80  
 F +32 89 81 97 90  
 M mailbox@kreon.com  
 www.kreon.com


It is possible that the  
 product images do not  
 match the selected  
 configuration

<b>illuminant</b>	
output	840lm
CCT	2700K
CRI	98
lamptype	LED
symbol	
wattage	2x10,6W
voltage	230V
rotation/inclination	360°/30°
beam angle	spot (17°)

Combinations can be specified on order form.  
 The coverplates on the inside of the profile are always black  
 Only one optional accessory per luminaire.


# kreon specification sheet

<b>required accessories</b>	
<b>tracks and profiles</b>	KR775201   Cana 80 recessed mounted profile, white
<b>general information</b>	
ip classification	40
input voltage	230V
dimming	DALI
<b>full dimensions</b>	
LxWxH	max. 6000mm x 102mm x 140mm
<b>material and surface</b>	
profile	
material	aluminium, extruded
colour	white / black
<b>cut-out dimensions</b>	
<b>in plasterboard</b>	
LxWxH	L x 125mm x 185mm
panel	max. 26mm
<b>remarks</b>	
The profile is supplied pre-assembled	
Max. length of a single run profile = 6000mm. Shipping length depends on transport possibilities.	



# kreon specification sheet

<b>tracks and profiles</b>	KR775202   Cana 80 recessed mounted profile, black
<b>general information</b>	
ip classification	40
input voltage	230V
dimming	DALI
<b>full dimensions</b>	
LxWxH	max. 6000mm x 102mm x 140mm
<b>material and surface</b>	
profile	
material	aluminium, extruded
colour	black / black
<b>cut-out dimensions</b>	
<b>in plasterboard</b>	
LxWxH	L x 125mm x 185mm
panel	max. 26mm
<b>remarks</b>	<p>The profile is supplied pre-assembled</p> <p>Max. length of a single run profile = 6000mm. Shipping length depends on transport possibilities.</p>



<b>plasterkits</b>	KR705010   trimless plasterkit profile
<b>material and surface</b>	
plasterkits	
material	aluminium, extruded
<b>cut-out dimensions</b>	
<b>in plasterboard</b>	
panel	max. 26mm
<b>remarks</b>	The profile must be finished with polyester gypsum.