




kreon specification sheet

your selection	KR934900-8527-SW ligna 40 in-cana, LED (HE)
KR755201	tracks and profiles Cana 40 profile, white
KR755202	tracks and profiles Cana 40 profile, black
product	KR934900-8527-SW ligna 40 in-cana, LED (HE)
general information	
application	luminaire for recessed or surface mounted profile
direction of mounting	↓
protection class	3
ip classification	40
input voltage	24Vdc
dimming	ON-OFF
visible dimensions	
LxW	min. 600mm x 50mm
steps	50mm
illuminant	
output	921lm/m
CCT	2700K
CRI	85+
lamptype	LED
symbol	
wattage	11,6W/m
voltage	24Vdc




kreon nv
 Industrieweg Noord 1152
 3660 Oudsbergen
 Belgium
 T +32 89 81 97 80
 F +32 89 81 97 90
 M mailbox@kreon.com
 www.kreon.com

It is possible that the
 product images do not
 match the selected
 configuration

kreon specification sheet

required accessories	
tracks and profiles	KR755201 Cana 40 profile, white
general information	
ip classification	40
input voltage	230V
full dimensions	
LxWxH	max. 6000mm x 54mm x 80mm
material and surface	
profile	
material	aluminium, extruded
colour	white / black
cut-out dimensions	
in plasterboard	
LxWxH	L x 75mm x 115mm
remarks	
The profile is supplied pre-assembled	
Max. length of a single run profile = 6000mm. Shipping length depends on transport possibilities.	



tracks and profiles	
tracks and profiles	KR755202 Cana 40 profile, black
general information	
ip classification	40
input voltage	230V
full dimensions	
LxWxH	max. 6000mm x 54mm x 80mm
material and surface	
profile	
material	aluminium, extruded
colour	black / black
cut-out dimensions	
in plasterboard	
WxH	75mm x 115mm
pending height	2,5m
panel	max. 26mm
remarks	
The profile is supplied pre-assembled	
Max. length of a single run profile = 6000mm. Shipping length depends on transport possibilities.	

