



# kreon specification sheet

<b>product</b>	KR952112-9027-SP-   up 40, black
<b>general information</b>	
application	recessed luminaire for floors
direction of mounting	↑
protection class	3
ip classification	67
ik classification	06
electric gear	not included
<b>visible dimensions</b>	
LxW	50mm x 50mm
<b>full dimensions</b>	
LxWxD	50mm x 50mm x 43mm



**kreon nv**  
 Industrieweg Noord 1152  
 3660 Oudsbergen  
 Belgium  
 T +32 89 81 97 80  
 F +32 89 81 97 90  
 M mailbox@kreon.com  
 www.kreon.com

It is possible that the  
 product images do not  
 match the selected  
 configuration

<b>illuminant</b>	
output	149lm
CCT	2700K
CRI	90+
drive current	700mA
lamptype	LED
symbol	
wattage	2W
<b>configuration options</b>	
beam angle	spot
installation	floor installation (standard)
<b>material and surface</b>	
housing	
material	aluminium, turned
colour	black
surface treatment	anodised
frame	
material	stainless steel
colour	black
glass cover	
material	glass
colour	black
<b>cut-out dimensions</b>	

# kreon specification sheet

<b>in plasterboard</b>	
panel	9-18mm
<b>in massive element</b>	
LxWxD	45mm x 45mm (XC = 47mm) x 60mm

Driver must be placed on remote.