## **kreon** specification sheet

your selection	KR <b>952712  </b> up 80 circular gherkin
KR <b>772753</b>	gear   LED driver, 700mA, DALI, 35W (IP68)
product	KR <b>952712</b>   up 80 circular gherkin
general information	
application	recessed luminaire for floors
direction of mounting	<b>↑</b>
ip classification	67
power	8,4W
electric gear	not included
visible dimensions	
height	~200-250mm
full dimensions	
HxD	~200-250mm x 70
diameter	95mm





kreon nv Industrieweg Noord 1152 3660 Oudsbergen Belgium T +32 89 81 97 80 F +32 89 81 97 90 M mailbox@kreon.com www.kreon.com

It is possible that the product images do not match the selected configuration

illuminant	
output	152lm
colour temperature	2700K
CRI	80+
drive current	700mA
lamptype	LED
symbol	<u> </u>
wattage	8,4W
cut-out dimensions	
in plasterboard	
depth	84mm
diameter	86mm
in massive element	
depth	84mm
diameter	86mm

## **kreon** specification sheet

The stated dimensions are only to be used as a reference. Actual dimensions may vary. Each unit is unique due to the artisanal production technique.

optional accessories	
gear	KR <b>772753</b>   LED driver, 700mA, DALI, 35W (IP68)
general information	
ip classification	68
drive current	700mA