## **kreon** specification sheet

your selection	KR <b>962312-9027-SP</b>   holon 40 directional recessed mounted, LED, black
KR707104	plasterkits   plasterkit
NR707104	piasterkits   piasterkit
product	KR <b>962312-9027-SP</b>   holon 40 directional recessed mounted, LED, black
general information	·
application	semi-recessed luminaire for ceilings
direction of mounting	<u>↓</u>
protection class	3
ip classification	40
certification	CE
electric gear	not included
visible dimensions	
height	155mm
diameter	45mm
illuminant	FFOIr.
output CCT	2700K
CRI	90+
drive current	700mA
lamptype	LED
symbol	
5,26.	<u> </u>
wattage	8,4W
rotation/inclination	355°/90°
beam angle	spot (20°)
material and surface	
lamp housing	
material	aluminium, turned
colour	black
surface treatment	powdercoated
cut-out dimensions	
in plasterboard	
height	35mm
diameter	63mm





kreon nv Industrieweg Noord 1152 3660 Oudsbergen Belgium T +32 89 81 97 80 F +32 89 81 97 90 M mailbox@kreon.com www.kreon.com

It is possible that the product images do not match the selected configuration

CRI80 available until end of stock

## **kreon** specification sheet

required accessories	
plasterkits	KR707104   plasterkit
general information	
certification	CE
cut-out dimensions	
in plasterboard	
diameter	63 mm
panel	9-14

