



# kreon specification sheet

<b>your selection</b>	KR962711-9027-FL   holon 40 directional in-nuit, LED, white
KR703215	tracks and profiles   Nuit profile, gear incl., white/black
KR703031	gear   LED driver, phase dimmable
<b>product</b>	KR962711-9027-FL   holon 40 directional in-nuit, LED, white
<b>general information</b>	
application	luminaire for recessed or surface mounted profile
direction of mounting	→↓
ip classification	40
electric gear	not included
<b>full dimensions</b>	
length	150mm
diameter	45mm
<b>illuminant</b>	
output	558lm
CCT	2700K
CRI	90+
drive current	700mA
lamptype	LED
symbol	
wattage	8,4W
rotation/inclination	355°/90°
beam angle	flood (30°)



**kreon nv**  
 Industrieweg Noord 1152  
 3660 Oudsbergen  
 Belgium  
 T +32 89 81 97 80  
 F +32 89 81 97 90  
 M mailbox@kreon.com  
 www.kreon.com

It is possible that the  
 product images do not  
 match the selected  
 configuration

# kreon specification sheet

<b>required accessories</b>	
<b>tracks and profiles</b>	KR703215   Nuit profile, gear incl., white/black
<b>general information</b>	
application	surface-mounted profile for ceilings
input voltage	230V
dimming	1-10V / DALI / phase dimming
<b>full dimensions</b>	
LxWxH	min. 900mm/max. 4000mm x 42,5mm x 60mm
<b>material and surface</b>	
profile	
material	aluminium, extruded
surface treatment	powdercoated
colour	white / black
remarks	Max. length of a single run profile = 4000mm. Shipping length depends on transport possibilities. Fixation point every 2,3m The profile is supplied pre-assembled
<b>gear</b>	
	KR703031   LED driver, phase dimmable