kreon specification sheet

your selection	KR 962711-9027-SP holon 40 directional in-nuit, LED, white
KR703215	tracks and profiles Nuit profile, gear incl., white/black
KR703031	gear LED driver, phase dimmable
product	KR 962711-9027-SP holon 40 directional in-nuit, LED, white
general information	
application	luminaire for recessed or surface mounted profile
direction of mounting	\rightarrow \downarrow
ip classification	40
electric gear	not included
full dimensions	
length	150mm
diameter	45mm
illuminant	
output	558Im
ССТ	2700К
CRI	90+
drive current	700mA
lamptype	LED
symbol	<u> </u>
wattage	8,4W
rotation/inclination	355°/90°
beam angle	spot (20°)





3660 Oudsbergen
Belgium
T +32 89 81 97 80
F +32 89 81 97 90
M mailbox@krean.com
www.krean.com
It is possible that the
product images do not
match the selected
configuration

kreon nv Industrieweg Noord 1152

kreon specification sheet

required accessories	
tracks and profiles	KR703215 Nuit profile, gear incl., white/black
general information	
application	surface-mounted profile for ceilings
input voltage	230V
dimming	1-10V / DALI / phase dimming
full dimensions	
LxWxH	min. 900mm/max. 4000mm x 42,5mm x 60mm
material and surface	
profile	
material	aluminium, extruded
surface treatment	powdercoated
colour	white / black
remarks	
	Max. length of a single run profile = 4000mm. Shipping length depends on
	transport possibilities.
	Fixation point every 2,3m
	The profile is supplied pre-assembled
	KR703031 LED driver, phase dimmable
gear	KK/U3U31 LED Gilver, phase diminable