


kreon specification sheet

your selection	KR974112-9027 lini 10 profile, black
KR774010	installation accessories mounting clip
KR774210	plasterkits recessed trimless plasterkit
product	KR974112-9027 lini 10 profile, black
general information	
application	surface-mounted profile for ceilings
direction of mounting	↓
protection class	3
ip classification	44
electric gear	not included
full dimensions	
WxH	15mm x 24mm
illuminant	
output	512lm/m
CCT	2700K
CRI	90+
lamptype	LED
symbol	
wattage	14,4W/m
voltage	24V



kreon nv
 Industrieweg Noord 1152
 3660 Oudsbergen
 Belgium
 T +32 89 81 97 80
 F +32 89 81 97 90
 M mailbox@kreon.com
 www.kreon.com

It is possible that the product images do not match the selected configuration

Profile length needs to be optimised in steps of 50mm. Length to be configured. No dark spots allowed. No more than 5m can be powered in series, longer lengths to be connected to the power supply in parallel. Use power supply on remote.
 Minimum 111mm, max. length of a single run profile 2961mm, profile sections can be connected.
 All profiles are custom made and supplied pre-assembled.

required accessories	
installation accessories	KR774010 mounting clip
remarks	Sold per 5 pieces. In case of surface mounted use: 2 clips per meter

kreon specification sheet

plasterkits	KR774210 recessed trimless plasterkit
remarks	Plasterkit profile should be finished with polyester gypsum. Possible thickness of board material: 12,5/15/18mm
