

kreon specification sheet

your selection	KR974190-9027-FL nuit profile 1x5 LED module
KR703211	tracks and profiles Nuit profile, gear incl., white
KR703021	gear LED driver, phase dimmable
product	KR974190-9027-FL nuit profile 1x5 LED module
general information	
application	luminaire for recessed or surface mounted profile
direction of mounting	↓
ip classification	20
input voltage	230V
power	7W
electric gear	not included
fixture dimensions	
length	250mm
illuminant	
output	585lm
CCT	2700K
CRI	90+
drive current	500mA
lamptype	LED
symbol	
wattage	7W
beam angle	flood (29°)
voltage	230V



kreon nv
 Industrieweg Noord 1152
 3660 Oudsbergen
 Belgium
 T +32 89 81 97 80
 F +32 89 81 97 90
 M mailbox@kreon.com
 www.kreon.com

It is possible that the
 product images do not
 match the selected
 configuration

kreon specification sheet

required accessories	
tracks and profiles	KR703211 Nut profile, gear incl., white
general information	
application	surface-mounted profile for ceilings
input voltage	230V
dimming	1-10V / DALI / phase dimming
full dimensions	
LxWxH	min. 900mm/max. 4000mm x 42,5mm x 60mm
material and surface	
profile	
material	aluminium, extruded
surface treatment	powdercoated
colour	white
remarks	Max. length of a single run profile = 4000mm. Shipping length depends on transport possibilities. Fixation point every 2,3m The profile is supplied pre-assembled
gear	
	KR703021 LED driver, phase dimmable
general information	
dimming	phase dimming