

kreon specification sheet

| | |
|----------------------------|---|
| your selection | KR974190-9027-SP nuit profile 1x5 LED module |
| KR703215 | tracks and profiles Nuit profile, gear incl., white/black |
| KR703021 | gear LED driver, phase dimmable |
| product | KR974190-9027-SP nuit profile 1x5 LED module |
| general information | |
| application | luminaire for recessed or surface mounted profile |
| direction of mounting | ↓ |
| ip classification | 20 |
| input voltage | 230V |
| power | 7W |
| electric gear | not included |
| fixture dimensions | |
| length | 250mm |
| illuminant | |
| output | 585lm |
| CCT | 2700K |
| CRI | 90+ |
| drive current | 500mA |
| lamptype | LED |
| symbol |  |
| wattage | 7W |
| beam angle | spot (12°) |
| voltage | 230V |



kreon nv
 Industrieweg Noord 1152
 3660 Oudsbergen
 Belgium
 T +32 89 81 97 80
 F +32 89 81 97 90
 M mailbox@kreon.com
 www.kreon.com

It is possible that the
 product images do not
 match the selected
 configuration

kreon specification sheet

| | |
|-----------------------------|---|
| required accessories | |
| tracks and profiles | KR703215 Nuit profile, gear incl., white/black |
| general information | |
| application | surface-mounted profile for ceilings |
| input voltage | 230V |
| dimming | 1-10V / DALI / phase dimming |
| full dimensions | |
| LxWxH | min. 900mm/max. 4000mm x 42,5mm x 60mm |
| material and surface | |
| profile | |
| material | aluminium, extruded |
| surface treatment | powdercoated |
| colour | white / black |
| remarks | Max. length of a single run profile = 4000mm. Shipping length depends on transport possibilities. Fixation point every 2,3m The profile is supplied pre-assembled |
| gear | |
| | KR703021 LED driver, phase dimmable |
| general information | |
| dimming | phase dimming |