


kreon specification sheet

product	KR982321-9827- up in-line 165, anti glare, gear excl., white
general information	
application	recessed luminaire for floors
direction of mounting	↑
protection class	3
ip classification	67
ik classification	10
surface temperature	50°C
incl. cable	1m
input voltage	230V
electric gear	not included
visible dimensions	
LxW	155 mm x 155mm
full dimensions	
LxWxD	155mm x 155mm x 97mm
illuminant	
output	544lm
CCT	2700K
CRI	98
drive current	700mA
lamptype	LED
symbol	
wattage	12,9W
beam angle	28°
configuration options	
use	standard
material and surface	
housing	
material	aluminium, die-cast
colour	black
surface treatment	cataphoretically painted
material	stainless steel
colour	silver, matt
glass cover	
material	glass
colour	white
glass cover	
inclosed	anti-glare louvre
cut-out dimensions	



kreon nv
 Industrieweg Noord 1152
 3660 Oudsbergen
 Belgium
 T +32 89 81 97 80
 F +32 89 81 97 90
 M mailbox@kreon.com
 www.kreon.com

It is possible that the
 product images do not
 match the selected
 configuration

kreon specification sheet

in massive element

LxWxD	156mm x 156mm x 97mm
panel	6-35mm

Surface temperature at 25 °C ambient temperature