




kreon specification sheet

your selection	KR991432-9027-P2 oran pendant kap stone, long cylinder, black, gear excl.
KR791100	installation accessories recessed suspension kit
KR707122	louvres louvre aplis in-line 40 black
KR791002	installation boxes surface mounted installation box, black Ø 45 H 50

product	KR991432-9027-P2 oran pendant kap stone, long cylinder, black, gear excl.
----------------	---

general information	
application	pendant
direction of mounting	↓
protection class	3
ip classification	40
electric gear	not included
full dimensions	
length	286mm
diameter	282mm
pending height	max. 3000mm
illuminant	
output	315lm
CCT	2700K
CRI	90+
drive current	700mA
lamptype	LED
symbol	
wattage	6,7W



kreon nv
 Industrieweg Noord 1152
 3660 Oudsbergen
 Belgium
 T +32 89 81 97 80
 F +32 89 81 97 90
 M mailbox@kreon.com
 www.kreon.com

It is possible that the product images do not match the selected configuration

configuration options	
shade	black shade bottom

Lumen output may vary due to the use of natural products.
 Protect the alabaster block against direct sunlight and temperatures above 50°C.

required accessories	
installation accessories	KR791100 recessed suspension kit

kreon specification sheet

louvres	KR707122 louvre aplis in-line 40 black
general information	
certification	CE
material and surface	
frame	
material	aluminium, die-cast
surface treatment	powdercoated
colour	black
installation boxes	KR791002 surface mounted installation box, black Ø 45 H 50

