



AQUATRAP® LGR DEHUMIDIFIER

Stackable | Efficient | Competitively Priced

AT150RS

AT150RS

The AT150RS portable LGR dehumidifier from Abatement Technologies® is designed to make your structural drying work faster and your bottom line healthier.

FEATURES & BENEFITS

- Units may be stacked up to two high for space saving storage
- Folding handle is easily moved out of the way
- "No tools" filter changes
- Discharge hose equipped with quick connects on both ends
- Control panel is recessed for protection
- Handles are located on front and above wheels for easy lifting
- Soft-start compressor cycle reduces startup load
- Meets CSA / UL standards



XACTIMATE CODE: WTR-DHM>
XACTIMATE PRODUCT CATEGORY: LGR

TECHNICAL SPECIFICATIONS

DESCRIPTION	UNIT	AT150RS
Water Removal	-	(90° F/90% RH) 140 Pints/66L per day @ AHAM (80° F/60% RH) 74 Pints/35L per day
Operating temperature range	°F (°C)	34° - 100° (1.1° - 37.8°)
Refrigerant	-	R410A
Max Power Consumption	W	850 Watt
Voltage/Cycle	V / Hz	115V / 60Hz
Amperage	A	7.5A max
Rated Air Flow	-	354CFM / 600m ³ /h
Control Panel	-	Touchpad
Defrost Type	-	Sensor Controlled Thermodynamic Defrost
Air Filter	-	Pleated Filter (P/N: AT250FLTR)
Water Pump	-	Centrifugal
Housing	-	Rotomolded Plastic
Drain Hose Length	ft (m)	32 (10)
Cord Length	ft (m)	26 (8)
Dimensions (L x W x H)	in (cm)	1.6 x 19.6 x 33.5 (50 x 50 x 85)
Weight	lb (kg)	87 (39.5)

Specifications and details are subject to change without prior notice.

CONTACT US FOR MORE INFORMATION



USA
1-800-634-9091
ABATEMENT.COM
IAQINFO@ABATEMENT.COM

CANADA
1-800-827-6443
ABATEMENT.CA
IAQINFO@ABATEMENT.CA

THE AT150RS IS BEST SUITED FOR:



DISASTER RESTORATION



ABATEMENT & REMEDIATION



HEALTHCARE CONSTRUCTION



HEALTHCARE FACILITIES