



CNAS L0413

Page 1 of 7

Date: 2021-08-31 No.: HC21060353

Applicant(Code:01325900): Savewo Limited

1/F

266-270 Texaco Road Tsuen Wan NT HK

Description of Sample(s) : One submitted sample said to be Savewo 3DMask Ultra.

Country of Origin: Hong Kong

Sample(s) Received Condition(s): In intact original package under

ambient temperature

Date Sample(s) Received : 2021-06-08

Date Tested 2021-08-18 to 2021-08-27 L S L L

Investigation Requested : Performa

: Performance Test as per EN 14683:2019 + AC:2019

1. Bacterial Filtration Efficiency (BFE) %
- Staphylococcus aureus (ATCC 6538)

2. Differential pressure

3. Microbial cleanliness (Bioburden)

4. Splash resistance

Remark(s) : Tests were conducted on the sample after accelerated aging at 60°C for

65 days according to ASTM F1980.





Date : 2021-08-31 Page 2 of 7

No. : HC21060353

Requirement

Performance Test as per EN 14683:2019 + AC:2019	Type I	Type II	Type IIR	
Bacterial Filtration Efficiency(BFE) %	≥95%	≥98%		
- Staphylococcus aureus (ATCC 6538)	aureus (ATCC 6538)			
Breathability (Differential pressure)	<40 Pa/cm ² <60 Pa/cr		<60 Pa/cm ²	
Microbial Cleanliness (Bioburden)		≤30 cfu/g	X	
Splash Resistance	Not Re	equired	Pass at	
CCT VCADICIT V	CADECE	$\Gamma = W C \Lambda$	≥16.0kPa	
ESEE V CARESEE V	CARESE	E V LA	(≥120 mmHg)	

<u>Summary:</u>

Performance Test as per EN 14683:2019 +	Savewo 3DMask Ultra Type IIR		
AC:2019			
Bacterial Filtration Efficiency (BFE) % - Staphylococcus aureus (ATCC 6538)	Pass		
Breathability (Differential pressure)	Pass		
Microbial Cleanliness (Bioburden)	Pass		
Splash Resistance	Pass		



Date: 2021-08-31 Page 3 of 7

No. : HC21060353

Test Result(s):

1. Bacterial Filtration Efficiency (BFE) %

Test method: EN 14683:2019 + AC:2019, Annex B

Summary: The BFE test is performed to determine the filtration efficiency of test articles by comparing the bacterial countrol counts upstream of the test article to the bacterial counts downstream. A suspension of Staphylococcus aureus was aerosolized using a nebulizer and delivered to the test article at a constant flow rate and fixed air pressure. The challenge delivery was maintained at $1.7 - 3.0 \times 10^3$ colony forming units (CFU) with a mean particle size (MPS) of $3.0 \pm 0.3 \mu m$. The aerosols were drawn through a six-stage, viable particle, Andersen sampler for collection. This test method complies with EN 14683:2019 + AC:2019, Annex B

All test method acceptance criteria were met.

Specimen(s)	Savewo 3DMask Ultra
1	99.9%
2	99.7%
3	>99.9%
4	>99.9%
5	>99.9%

Notes: - Challenge bacteria: Staphylococcus aureus (ATCC 6538)

Positive control average: 1949 CFU
 Negative control average: <1 CFU

- Mean particle size : 3.1μm
- Testing side : Outside of specimen

- Testing area: 49 cm²

- Precondition: Minimum of 4 hours at (21±5) °C and (85±5) % relative humidity (RH)



Date: 2021-08-31 Page 4 of 7

No. : HC21060353

2. Differential Pressure

Test method: EN 14683:2019 + AC:2019, Annex C

Summary: The Differential Pressure test is performed to determine the breathability of test articles by measuring the differential air pressure on either side of the test article using a manometer, at a constant flow rate. This test complies with EN 14683:2019 + AC:2019, Annex C.

All test method acceptance criteria were met.

			Test a	ırea (in Pa	/cm²)		Ave	rage
ij T	Specimen(s)	1	2	3	4	5	Pa/cm ²	mmH ₂ O/cm ²
		42.4	43.9	51.7	43.5	51.5	46.5	4.7.1
	2	48.2	45,3	<i>5</i> 1.1	43.4	46.1	46.8	4,8
	3	46.0	48.1	47.0	43.6	53.3	47.6	4.9
	4	44.9	48.7	48.4	44.6	48.9	47.1	4.8
	5	47.4	48.1	52.2	45.8	47.0	48.1	4.9

Notes: $-1 \text{ mmH}_2\text{O/cm}^2 = 9.8 \text{ Pa/cm}^2$

- Flow rate: 8 Litre/min

- Precondition: Minimum of 4 hours at (21±5) °C and (85±5) % relative humidity (RH)



Date: 2021-08-31 Page 5 of 7

No. : HC21060353

3. Microbial cleanliness (Bioburden)

Test method: EN 14683:2019 + AC:2019, Annex D and EN ISO 11737-1:2018

Summary: The full mask is aseptically removed from the packaging and placed in a sterile 500ml bottle containing 300ml extraction liquid and shake for 5 min at 250 rpm. 100 ml of the extraction liquid is filtered through a 0.45µm filter and laid down on a TSA plate for the total viable aerobic microbial count. Another 100ml aliquot of the same extraction liquid is filtered in the same way and the filter plated on Sabouraud Dextrose agar (SDA) with chloramphenicol for fungi enumeration. The plates are incubated for 3 days at 30°C and 7 days at (20 to 25)°C for TSA and SDA plates respectively. The total bioburden is expressed by addition of the TSA and SDA counts. This test complies with EN14683:2019 + AC:2019, Annex D and EN ISO 11737: 2018.

All test method acceptance criteria were met.

Specimen(s) Mask Weight (g) Total Bioburden Total Bioburden (CFU/mock)

Specifical(s)	wask weight (g)	(CFU/mask)	(CFU/g)
1	4.14	0	0
2	4.11	0	0
3	4.12	0	0
4	4.13	0	0
5	4.14	0	0
		Mean:	0

Notes: - CFU denotes Colony Forming Unit

- EN 14683:2019 + AC:2019 requirement: ≤ 30 CFU/g



Date: 2021-08-31 Page 6 of 7

No. : HC21060353

4. Synthetic Blood Penetration

Test method: ISO 22609:2004

Summary: This procedure was performed to evaluate surgical facemasks and other types of protective clothing materials designed to protect against fluid penetration. The purpose of this procedure is to simulate an arterial spray and evaluate the effectiveness of the test article in protecting the user from possible exposure to blood and other body fluids. The distance from the target area surface to the tip of the cannula is 30.5cm. A test volume of 2 mL of synthetic blood was employed using the targeting plate method.

This test method was designed to comply with ISO 22609:2004 (as referenced in EN14683:2019 + AC:2019) with the following exception: ISO 22609:2004 requires testing to be performed in an environment with a temperature of (21±5)°C and (85±5)% relative humidity (RH). Instead, testing was performed at ambient conditions within one minute of removal from the environmental chamber held at those parameters.

All test method acceptance criteria were met.

Test Pressure: ≥120mmHg

Specimen Number	Savewo 3DMask Ultra		
1-5, 7-22, 24-31	None Seen		
6, 23, 32	Seen		

Requirement:

An acceptable quality limit of 4.0% is met for a normal single sampling plan when \geq 29 of 32 test specimens show passing result (none seen)

Notes: - Test Side: Outside

- Precondition : Minimum of 4 hours at (21 \pm 5) °C and (85 \pm 5) % relative humidity (RH)



Date: 2021-08-31 Page 7 of 7

No. : HC21060353

Photo(s):





***** End of Test Report *****

Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by The Hong Kong Standards & Testing Centre Limited (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The Company provides its services on the basis that such terms and conditions constitute express agreement between the Company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by the Company as a result of this application for testing service (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to his customer, supplier or other persons directly concerned. Subject to clause 3, the Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall be at liberty to disclose the testing-related documents and/or files anytime to any third-party accreditation and/or recognition bodies for audit or other related purposes. No liabilities whatsoever shall attach to the Company's act of disclosure.
- 4. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 5. The results in Report apply only to the sample as received and do not apply to the bulk, unless the sampling has been carried out by the Company and is stated as such in the Report.
- 6. When a statement of conformity to a specification or standard is provided, the ILAC-G8 Guidance document (and/or IEC Guide 115 in the electrotechnical sector) will be adopted as a decision rule for the determination of conformity unless it is inherent in the requested specification or standard, or otherwise specified in the Report.
- 7. In the event of the improper use the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 8. Sample submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 9. The Company will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 10. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 11. Subject to the variable length of retention time for test data and report stored hereinto as to otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of this test report for a period of three years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after the retention period. Under no circumstances shall we be liable for damages of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.
- 12. Issuance records of the Report are available on the internet at www.stc.group. Further enquiry of validity or verification of the Reports should be addressed to the Company.