

GREASE DISPENSE HANDLES



413 080

High pressure grease dispenses handle with ergonomic body and trigger designed to reduce operator hand fatigue. Manufactured in aluminum with steel insert for high pressure.
 Maximum working pressure: 8,000 psi.
 Inlet thread: 1/4" NPTF.
 Outlet thread: 1/8" NPTF.

Part No. 413 077

Grease control handle with rigid outlet and 3 jaw coupler (PN 121 050).

Part No. 413 080

Grease control handle with z-swivel, rigid outlet and 3 jaw coupler (PN 121 050).

Part No. 413 081

Grease control handle with 18" double steel braid reinforced rubber hose and 3 jaw coupler (PN 121 050).

Part No. 413 082

Grease control handle with z-swivel and 18" double steel braid reinforced rubber hose with 3 jaw coupler (PN 121 050).



1177

ELECTRONIC-METERED GREASE DISPENSE HANDLE

Part No. 1177

Same as Part No. 413 082, except with 411 103 grease meter.

DOUBLE STEEL BRAID GREASE OUTLET HOSES

Maximum working pressure 7,000 psi.
 1/8" NPTM threads.

GREASE OUTLET HOSES ONLY	
PART No.	LENGTH
140 030	12"
140 050	18"

GREASE OUTLET HOSES WITH 3 JAW CONNECTOR	
PART No.	LENGTH
142 030	12"
142 050	18"

GREASE CONTROL HANDLE SWIVELS



Equipped with ball bearings for easy articulation even at high pressure. For best results, use a straight swivel between the pump and distribution hose and Z-swivel between the hose and grease control gun.
 Maximum working pressure: 8,000 psi.

- 1104** "Z" inlet swivel. 1/4" NPTM x 1/2"-27M.
- 1105** "Z" inlet swivel. 1/4" NPTM x 1/4" NPTF.
- 1108** Straight swivel. 1/4" NPTM x 1/2"-27M.
- 1109** Straight swivel. 1/4" NPTM x 1/4" NPTF.

GREASE CONTROL GUN OUTLETS



Part No. 1122
 Rigid outlet with 3 jaw hydraulic grease coupler. (PN 121 050).

Part No. 1120
 Rigid outlet.