Giant Tire Bead Breaker Head - Use on 5-Piece Rims 25" - 51"

Model #10104



- Ram Assembly Part #10216 10" Stroke
- Frame Assembly
- Wedges
- Use on 5-piece rims 25" to 51" without pry bar/ bead loosening pockets.
- Replaces Goodyear TO-100-HA.
- Stroke: 10" | 254mm
- Includes #10216 Ram Assembly, #10215 Frame Assembly, and Wedges.
- Weight: 68 lbs. | 31 kg



Point.Scan.Explore.



MODEL 10212

10104 - Bead Breaker

10500 - Turbo II Pump, Air Hydraulic, 3 1/2 Quart

10604 - Hose Assembly with Hose Coupler, 8' 10601K - Air Reducer, 6" Whip-Hose



Giant Tire Bead Breaker - For 39" Rims & Larger

Model #10103

OSHA



Plunger

Frame

Hook

25 Tons of Bead Breaking Force, 6" Stroke. | 152mm

Use on 5 piece rims 39", 45", 51", 57", and 63" wheel sizes.

In some cases you must first use #10105 or the #10100 bead breaker to start the movement of the rim flange; the #10103 can then be used.

- #10594, air/hydraulic pump is recommended for operation.
- The #10627 Kit converts the #10103 into a 10103L, which is capable of Working on 63" Rims.
- Weight: 54 lbs. | 25 kg



MODEL 10103

MODEL 10627 Kit on 10103

Point.Scan.Explore.



MODEL 10211





10103 - Giant Tire Bead Breaker Tool 10594 - Turbo Pump II, Air Hydraulic, 2 Gallon

10611 - 18' Hydraulic Hose 10605 - Male Coupler with female threads

10601K - Air Reducer, 6" Whip-Hose



