# **Cylcone X Series Bead Seaters**

MODELS 20390 & 20391



#### **Benefits & Features:**

Fast & Powerful Discharge System – Quickly releases air and seats tire Ergonomically Designed to support full control of tank while seating tire/wheel. "High-Force" Discharge Barrel – Designed for precise maximum air release for best seating of the bead the first time.

#### ASME Certified Tank

Safety glasses and ear protection included

#### sales@esco.net WWW.ESCO.NET 1.800.352.9852

#### 20390-20391SS.04.2020.A

## **Specifications:**

### MODELS 20390 & 20391



We Keep Your Equipment MOVING

The Cyclone X-Series Bead Seating Tank offers two models for small and medium applications. Both models are equipped with robust air tanks, casted out of steel and ASME certified. The Cyclone X-Series Bead Seaters supply a hassle-free, simple solution to seat the beads on equipment tires ranging from golf carts up to heavy duty and construction application. The Cyclone X-Series 5-gallon Bead Seating Tank is recommended for small and passenger tire application. The Cyclone X-Series 10-gallon Bead Seating Tank is recommended for most commercial tire sizes, skid steers and some tractor tires.

Model	TANK SIZE	RECOMMENDED AIR PRESSURE	MAX. PSI	DIMENSIONS	WEIGHT	BARCODE UPC
20390	5 Gallon	40-155 PSI	165 PSI	18 in. x 14.5 in. x 15 in. 457 x 368 x 381mm	31 lbs 14 kg	816904024734
20391	10 Gallon	40-155 PSI	165 PSI	24 in. x 16.5 in. x 17 in. 609 x 419 x 432mm	<b>46 lbs</b> 21 kg	816904024741

All Bead Seater Tanks are Covered by a 1-Year Warranty Against Manufacturer Defects



You Tube

**High-Force 2" Barrell** designed for maximum air release



**Ergonomically Designed Handle** positioning to support full control of tank while seating tire/wheel.



Protective Rubber Coated Feet protrect tank from daily use around the shop.

NOTE: ESCO reserves the right to change, alter, or modify product(s) without notice. This includes but is not limited to product: color, design, parts, accessories, etc.

sales@esco.net WWW.ESCO.NET 1.800.352.9852

