





Temperature +41°F to +122°F	Construction	Equipped with Manual drain
	Body: Aluminum Polycarbonate bowl with metallic protection	



### ALTO 3 - 1/2" HP REGULATOR

		<b>A (inch)</b>	<b>B (inch)</b>	<b>C (inch)</b>	<b>NPT female thread</b>	<b>Flow rate (cfm at 87 psi ΔP=14psi)</b>	<b>Max operating pressure (psi)</b>	<b>Part Numbers</b>
		2.795	6.299	-	1/2" FNPT	141.20	Inlet: 217 Outlet: 7-181	<b>TR HP203</b>
Pressure gauge port size: G 1/8								

### ALTO 3 - 1/2" HP FILTER-REGULATOR

		<b>A (inch)</b>	<b>B (inch)</b>	<b>C (inch)</b>	<b>NPT female thread</b>	<b>Flow rate (cfm at 87 psi ΔP=14psi)</b>	<b>Operating pressure (psi)</b>	<b>Filtration (µm)</b>	<b>Part Numbers</b>
		2.756	12.992	-	1/2" FNPT	105.96	Inlet: 290 Outlet: 7-181	40	<b>TM HP203</b>
Metallic vat without sight glass Pressure gauge part size: G 1/8									

### ALTO 3 - 1/2" DIVERTER BLOCK FOR OUTLETS WITHOUT OIL

		<b>A (inch)</b>	<b>B (inch)</b>	<b>NPT female thread</b>	<b>Air outlet</b>	<b>Part Numbers</b>
		2.874	3.661	1/2" FNPT	4 non-lubricated outlets	<b>TE 203</b>