

# STATICO

Global Supplier of Static Control & Cleanroom Products  
Tel: (650) 592-4733. 1-800-261-4149. Fax: 650-508-0761 Email: [sales2@statico.com](mailto:sales2@statico.com)  
541 Taylor Way, #1. San Carlos, CA 94070. USA. [www.statico.com](http://www.statico.com)

## *Product Information*

### *S1450 Series Two-Layer High Temperature Rubber Mat*



## *Description*

S1450 Series is a high performance two-layer rubber mat, with static dissipative surface in light green color and black conductive bottom layer. It is high temperature, solder and chemical resistant. This product is suitable for use for benches, floors, & trays, amongst other applications . Meets ANSI/ESD S20.20-2014.

## *Technical Data*

Resistance To Ground. ANSI/ESD S4.1	10E6-10E7
Surface Resistance. ANSI/ESD S4.1	10E6-10E8
Point To Point Resistance, Rp. IEC 61340-2-3	10E6-10E8
Resistance To Groundable Point, Rg. IEC 61340-2-3	10E6-10E7
Abrasion at 5 N Load. ISO 4649, Version A	150
Hardness. ISO 7619, Shore A	76
Residual Indentation. EN 433	0.1
Gloss (85 Degree). DIN EN ISO 2813	20 +/- 5
Part No.	S1450
Color	Light Green
Thickness (nominal)	0.080" (2mm)
Standard Roll Size *	48" X 32 feet (1.2mX10m)

\* Also available in Cut-To-Size.