

STATICO

Global Supplier of Static Control & Cleanroom Products
541 Taylor Way, Unit #1. San Carlos, CA 94070. USA. www.statico.com
Tel. (650)592-4733. 1-800-261-4149. Fax 650/508-0761. sales@statico.com

Model S2112

Wrist Strap Tester



Description

The S2112 is a precise device to perform on demand testing of all standard & conventional single conductor Wrist Grounding Straps for proper skin resistance, continuity, and the built-in safety resistor. NIST Certified. Meets ANSI/ESD S20.20-2014.

Specifications

Lo Fail (Red)	<800K Ω
Pass (Green)	800K Ω to 10M Ω
Hi Fail (Yellow)	> 10M Ω
Accuracy	+/- 5%
Test Voltage	9VDC
Operating Voltage	\geq 6.5 Volts < 9 Volts
Low Battery set at	6.5 Volts (Red LED indicator)
Operating Temperature	10 $^{\circ}$ C to 40 $^{\circ}$ C
Storage Temperature	-15 $^{\circ}$ C to + 60 $^{\circ}$ C
Relative Humidity	0% to 90% (None-Condensing)
Net Weight	3.15 oz (90 g)
Weight with 9V Battery	4.50 oz (127 g)
Dimensions (mm)	2-3/4" x 3.5" x 1-3/8"(70mm x 90mm x 28mm)

PS/S2112/Rev.2/215