

Product Specifications

S5900R Series

Anti Static Red Tape



Description

The new Red Anti-Static tape, S5900 Series is designed for general application in static free workstations. The product meets decay rate of MIL-B-81705, and is available on 3" (76mm +/-2mm) Paper Core, 54.6 Yards (50 Meters) Long Rolls.

Specifications

Base Material	Cellulose Film
Adhesive	Anti-Static Acrylic PSA
Color	Red
Thickness	50µm (0.05mm) +/-5µm
Rupture Elongation Factor (%)	60 +
Tensile Strength (Kg/cm ²)	4.5Kg 900 g/25 mm
Peel Adhesion (g/25mm)	600g (+/-50)
Temperature Resistance	70° C (158° F)
Surface Resistance (Film)	10E11 ohms/sq.
Surface Resistance (Adhesive)	10E11 ohms/sq.
Charge Decay Time	<2.0 Seconds
<u>Part No.</u>	<u>Width x Length</u>
S5912R	½" x 54.6 ((12mm x 50 m)

This product must be kept away from direct exposure to the sun light and shall be stored in a ventilated storage environment with temperature of 68° F (20° C).

NOTES

STATEMENTS, TECHNICAL INFORMATION, AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED ON TESTS WE BELIEVE TO BE RELIABLE BUT THEY ARE NOT TO BE CONSTRUED IN ANY MANNER AS WARRANTIES EXPRESSED OR IMPLIED. THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR HIS INTENDED USE AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER.