



# Product Specification Sheet

**Model No: CG6025L230-EC**

|                                 |  |
|---------------------------------|--|
| <b>Dimensions</b>               | 60x60x25mm                                 |
| <b>Bearing System</b>           | Dual Ball Bearing                          |
| <b>Wire Option</b>              | Bare wire input leads                      |
| <b>Connector Option</b>         | 3-Pin 2510 MOLEX (Female Housing/Male Pin) |
| <b>Rated Voltage</b>            | 230 VAC                                    |
| <b>Operating Voltage</b>        | 154 VAC~240 VAC                            |
| <b>Rated Operating Current</b>  | 0.03 Amp running                           |
| <b>Rated Speed</b>              | 2500 ±10% RPM                              |
| <b>Air Flow</b>                 | 25.73 CFM                                  |
| <b>Static Air Pressure</b>      | 7.08 mmH <sub>2</sub> O                    |
| <b>Noise Level</b>              | 31.2 dBA                                   |
| <b>Motor Protection Type</b>    | By Impedance With Polarity Protection      |
| <b>Environmental Protection</b> | None                                       |
| <b>Life Expectance</b>          | 67,000 Hours at 25°C                       |
| <b>Operation Temperature</b>    | -10°C to +70°C                             |
| <b>Net Weight</b>               | 54g  |
| <b>Options</b>                  | Closed Corners                             |

# DIMENSIONS DRAWING

