




(shown: optional FM2SP mount kit)



Lightning arrestor
LABH350NN
(sold separately)



FM2 Mount Kit
(sold separately)



**Elevation Pattern
(Y, Z, or H-Plane)**

FIBERGLASS BASE STATION ANTENNAS FEATURE INDUSTRY-LEADING DESIGN COMPONENTS THAT PERFORM IN EXTREME CONDITIONS

Laird Connectivity's fiberglass base station antennas are collinear designs enclosed in a high-density fiberglass, which is covered with a protective ultraviolet inhibiting coating. The radiating elements are made from high efficiency copper and are carefully phased to provide maximum gain in the horizontal plane. The mounting sleeves are tuned to eliminate RF currents from the transmission line, resulting in a "cold" sleeve allowing great freedom in mounting. This high quality and well-focused beam provides the highest gain and best efficiency.

FEATURES AND BENEFITS

- High Performance
- Easy installation w/ optional FM2SP
- Special UV treated radome, resists sun damage
- N-female industry standard connector
- 100% tested on a network analyzer

ELECTRICAL SPECIFICATIONS

Operating Frequency (MHz)	902-928
Number of Ports	1
VSWR – Max	<2.0:1
Gain (dBi)	2.15
Nominal Impedance (Ohms)	50
Max Power - Ambient 25°C (W)	100
Polarization	Vertical
Vertical Plane 3 dB Beamwidth	110°
Horizontal Plane 3 dB Beamwidth	360°

MECHANICAL SPECIFICATIONS

Dimensions – diameter x height – mm (inches)	33.02 x 339.72 (1.3 x 13-3/8)
Weight – kg (lbs.)	0.29 (.65)
Radome Material	Fiberglass
Lightning Protection	Lightning arrestor LABH350NN (sold separately)
Mounting	Optional FM2SP mounting kit (sold separately)

ENVIRONMENTAL SPECIFICATIONS

Operating Environment (Indoor or Outdoor)	Outdoor
Wind Operational – km/hr (mph)	210 (125)
Wind Operational with 0.5" radial ice – km/hr (mph)	137 (85)
Wind Resistance	0.1217 sq. ft.

CONFIGURATION

PART NUMBER	CABLE LENGTH	CONNECTOR
FG9020	N/A	N-Female



Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2020 Laird Connectivity, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

sales@lairdconnect.com
support@lairdconnect.com
www.lairdconnect.com

