

TECHNICAL DATA SHEET

BLUESTONE SEALER



DESCRIPTION

Rockstar BLUESTONE SEALER is a high-performance penetrating sealer which does not alter the appearance of the Stone. Developed for all Bluestone and Basalt tiles.

USES

Application of BLUESTONE SEALER onto bluestone pavers enhances the stain resistance of the bluestone surface without changing the colour or texture of the stone.

Rockstar BLUESTONE SEALER is ideal for Australian and Chinese sourced stone.

BENEFITS

- Excellent oil and water repellency, and stain resistance
- Does not change the look of the stone
- Does not inhibit the water-vapour permeability
- Rapid curing
- UV Stable

PROPERTIES

Appearance and colour.....	Colourless to yellowish, clear to hazy liquid
Specific Gravity (Water = 1).....	0.83 g/ml
Boiling Point.....	120 - 200°C
Solubility in Water.....	Not miscible
Flash Point.....	30°C

APPLICATION INSTRUCTIONS

1. Ensure the surface to be sealed is free of excess grout and is dry and free of any oils and other surface contaminants.
2. Apply BLUESTONE SEALER undiluted by lambswool applicator or low pressure hand sprayer. Ensure that the surface is fully saturated without leaving pools of material.
3. Apply a second coat once the first coat has dried (2-4 hours).
4. The product will cure in 12-24 hours depending on atmospheric conditions.

COVERAGE

Coverage is dependent on the permeability of the stone or tile and is in the range of 10-15 Mt² per Litre/50-150 ft² per Quart.

PRECAUTIONS

1. Do not allow pools of liquid BLUESTONE SEALER to dry on the surface. Remove excess liquid with a clean, lint-free cloth.
2. Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.

CLEANING

Clean all equipment with mineral turpentine.

PACKAGING

BLUESTONE SEALER is available in 1, 5 and 20 Litre Containers / 1 Quart / 1.32Gal / 5Gal.

STORAGE

Keep container tightly closed when not in use. Store in a cool, dry place out of reach of children.

Keep away from sources of heat, spark and ignition, product is flammable.

SAFETY

Classified as Hazardous according to criteria of Worksafe Australia. For further detailed information refer to Material Safety Data Sheet.