## **PRODUCT SPECIFICATION SHEET**

## **Plastic Firestopping Tag**

When applying a Firestop Label is a challenge or not possible, a Firestop Tag is a great alternative. You can either order our standard tag and fill out the critical information yourself or you can order a custom tag preprinted with your specific information. Our Firestop Tags are made of heavy-duty, waterproof, semi-rigid vinyl. Please contact us for your custom

FIRESTOP MATERIAL  5-3/4"  DO NOT TAMPER OR REMOVE  DATE INSTALLED: ASSEMBLY NO: PENETRATION BELONGS TO:  TO REPAIR OR RETROFIT CONTACT: COMPANY:	T	
FIRESTOP MATERIAL  5-3/4"  DO NOT TAMPER OR REMOVE  DATE INSTALLED: ASSEMBLY NO: PENETRATION BELONGS TO:  TO REPAIR OR RETROFIT CONTACT:		•
5-3/4"  DO NOT TAMPER OR REMOVE  DATE INSTALLED: ASSEMBLY NO: PENETRATION BELONGS TO:  TO REPAIR OR RETROFIT CONTACT:		WARNING
OR REMOVE  DATE INSTALLED:  ASSEMBLY NO:  PENETRATION BELONGS TO:  TO REPAIR OR  RETROFIT CONTACT:		FIRESTOP MATERIAL
ASSEMBLY NO:  PENETRATION BELONGS TO:  TO REPAIR OR  RETROFIT CONTACT:	5-3/4"	
RETROFIT CONTACT:		ASSEMBLY NO:
		RETROFIT CONTACT:
PHONE NUMBER:	<u> </u>	PHONE NUMBER:

Standard Size	5-3/4"x3" (146mm x 76mm), Custom shapes and sizes available
Installation Instructions	Hang to device or valve with one of our accessory options
Hole Dimensions	3/16" Brass Grommet
Service Temp	-40°F to 160°F (-40° C to 71°C)
Water Resistance	Excellent
Finish	Matte
Material Properties	.015" Semi-rigid vinyl with brass grommet in hole
Material Options	Dry erase laminate available , UV laminate available
Accessories Options	Zip ties, Stainless Steel Beaded Chain, Brass beaded chain
Color Options	Full color print available
Storage Stability	Indefinite when stored at 70°F (21°C) and 50% RH
Outdoor Durability	4 to 6 years, UV Resistant option available for outdoor use
Chemical Resistance	Resistant to Acids, Alkalis and Salts

TE	/	DD /	YYYY	JOB
ACTOR NAM	NAME			