## PRODUCT SPECIFICATION SHEET

## **Vinyl Firewall Sign**

Kolbi Firewall Signs are made of a heavy-duty 6mil vinyl with a high-strength adhesive to ensure the longevity of the product in its intended environment. In addition to being compliant with IBC 703.7 2018 Kolbi Firewall Signs can have important information added to the bottom of the sign such as; installing contractor info, building engineer contact information, and the Fire/Smoke barrier that is in place.



ring			
Overall Dimensions	10" High x 14" Wide		
Rating Text Size	3"		
Barrier Type Text Size	1"		

Standards Met	IBC (International Building Code) 703.7 2018				
Installation Instructions	Applied to a clean dry surface above 32°F (0°C)				
Service Temp	-40°F to 176°F (-40°C to 80°C)				
Water Resistance	Good, Product has passed submersion tests				
Finish	High Gloss				
Material Properties 6 Mil vinyl with pressure sensitive adhesive backing					
	Aggressive permanent acrylic adhesive				
Adhesive Properties	Stainless Steel 54 oz/in (594 N/m), Acrylic 56 oz/in (616 N/m)				
	Glass 53 oz/in (599 N/m), Polypropylene 51 oz/in (561 N/m) Expected Shear: 5 hours, Tack gm (740)				
Ink Properties	Inks resistant to fading with UV exposure, Semi-Gloss Finish				
Storage Stability	2 years stored at 70°F (21°C) and 50% RH				
Outdoor Durability	4 to 6 years				
Abrasion Resistance	Good				
Chemical Resistance	Resistant to Acids, Alkalis and Salts				
Equivalent To	Firewallsigns.com Firewall Sign, My Saftey Sign Firewall Sign, Seton Firewall Sign				

DATE _	ММ	/ DD	/	JOB	
CONTR	ACTOR NAME				