

Kolbi Conduit and Cable Wrap Around Pipe Markers are designed to meet engineering specifications for durability and safety. These pre-coiled, semi-rigid vinyl markers significantly reduce installation time by snapping onto pipes and go over moisture, dirt or grease without pipe preparation. Full wrap marker styles provide full 360 degree visibility for added safety.

**Conduit & Cable Wrap Around Marker Examples**



Style WAAA



Style WA

Style	Pipe OD (including insulation)	Marker length	Letter size
WAAA	Less Than 5/8" (15.88mm)	2-1/4" (57.15mm)	1/4" (6.35mm)
WAA	Less than 3/4" (19.05mm)	4" (101.6mm)	1/4" (6.35mm)
WA	3/4" - 1" (19.05mm - 25.4mm)	8" (203.2mm)	1/2" (12.7mm)
WB	1-1/8" - 2-3/8" (28.575mm - 60.33mm)	12" (304.8mm)	3/4" (19.05mm)
WC	2-1/2" - 3-1/4" (63.5mm - 82.55mm)	12" (304.8mm)	1-1/4" (31.7mm)
WD	3-3/8" - 4-1/2" (85.73mm - 114.3mm)	12" (304.8mm)	1-1/4" (31.7mm)

Color Combinations	
WHITE	WHITE
WHITE	BLACK
BLACK	WHITE
BLACK	Additional colors available

<b>Standards Met</b>	ANSI/ASME A13.1-2015 "Scheme for Identification of Piping Systems" ANSI Z535.1 "Safety Color Code"
<b>Installation Instructions</b>	No surface preparation necessary, Sizes WAAA to WE snap on and sizes WF thru WH strap on with nylon straps.
<b>Service Temperature</b>	-40°F to 180°F (-40° C to 82.22°C)
<b>Water Resistance</b>	Excellent
<b>Finish</b>	Matte Finish
<b>Material Properties</b>	.015" semi-rigid vinyl styles (WAAA to WB) .025" semi-rigid vinyl (styles WC to WD)
<b>Ink Properties</b>	Inks resistant to fading with UV exposure, Semi-Gloss Finish
<b>Storage Stability</b>	Indefinite at 70°F (21°C) and 50% RH
<b>Chemical Resistance</b>	Resistant to Acids, Alkalis and Salts
<b>Abrasion Resistance</b>	Good
<b>Outdoor Durability</b>	4 to 6 years, UV Resistant option available for outdoor use
<b>UV Resistant Option</b>	6+ Years
<b>Equivalent To</b>	Electromark Labels, Marker Services Coiled Conduit and Cable Markers, Brimar System 1 Voltage Markers

DATE MM / DD / YYYY

JOB

CONTRACTOR NAME