

## PMB Moisture Analyser



The PMB's fast response time and easy-to-use functionality make it the ideal moisture analyser for a range of different applications. The automatic test setting function lets you quickly run multiple tests without additional user input and the built-in memories lets you store that data for future reference. The PMB offers smart features that have been developed to give you the ultimate performance for moisture analysis.

PMB moisture balances sets a new standard for moisture analysis. Use the USB interface and connect a memory stick to download the results as they are taken and store them for future analysis, no need for additional software to take readings from the balance giving the user total freedom to collect data on a production floor or in the field.

With over 35 years of experience in the production of weighing instruments you can trust Adam for quality products that offer a range of features designed for a variety of applications.



**THE RIGHT BALANCE**  
Speed, Performance, Value

## PMB Highlights:

Navigating the built in applications is easy with the intuitively designed keypad. Access to the main functions is quick and a special lock out feature allows the supervisor to set up access to all or certain functions so users do not inadvertently change the settings. The colour coded keypad highlights the tare and start keys for easy recognition.

Multiple communications options lets you pick the right interface for your needs. USB or RS-232 both included as standard. Supports USB flash drive with automatic record keeping function to save each test result.

Store a range of procedures for different products that can be recalled at a touch of a button, to make setup and changing from one product to another simple.

## Technical Specifications

Model	PMB 53	PMB 202
Capacity	50g	200g
Readability	0.001g / 0.01%	0.01g / 0.05%
Repeatability (S.D.)*	0.005g / 0.05% (10g sample)	0.02g / 0.2% (10g sample)
Pan Size	90mm ø	
Temperature Range	50°C to 160°C in 1°C intervals	
Analysis Time	Max 99 minutes	
Program Timing	Manual shut off, Timed, Auto, Timed/Auto	
Weighing Units	g (grams), % M (percent moisture), % S (percent solids), ATRO % M (percent moisture / dry bases) ATRO % S (percent solids / dry bases)	
Languages	English, German, French, Spanish	
Stabilization Time	2-3 secs	
Interface	USB Host, USB I/O, RS-232	
Internal Memory	Up to 99 test results 49 Programmable user settings for configuration	
External Memory	External memory available with USB drive for additional configurations and to store test results	
Calibration	External	
Heating Element	Single 400W halogen heater	
Heating Options	Standard (one step) Step - up to 3 temp setting Ramp	
Display	Backlit LCD display with dual digits and capacity tracker, 24mm high digits	
Power Supply	Power cord, factory set for 110v or 220v 50/60hz	
Operating Temperature	32° -104°F / 0° - 40°C	
Overall dimensions	360 x 250 x 185mm (LxWxH)	
Net Weight	6kg	

\*Repeatability specifications percentage based upon 10g sample size.

The PMB makes moisture analysis easy for fast and accurate results.

## Features

- USB host for memory card and USB I/O interface
- RS-232 interface
- Built-in memories for storing products and settings
- 3 settings for heating sample, ramp up, step and standard
- Automatic test start setting for when the lid is closed
- Pan lifter to easily remove samples
- Large backlit display with dual text prompts
- Security locking slot for Kensington™ type lock and cable



## Accessories

- Kensington™ type lock and cable
- RS-232 cable
- USB cable
- USB Memory stick
- AdamDU Data collection software
- Adam printer
- Printer paper