robot @ coupe°

Blixer® 60



Number of 7 oz portions :	30 to 225 portions
Quantity processed per operation	13 to 99 lbs

A

SALES FEATURES

Blixer 60 is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

B TECHNICAL FEATURES

Blixer 60. 3-phase. Power 16 HP. 2 speeds. 100% stainless-steel appliance with 3 built in legs. Control panel with flush buttons and digital timer from 0 to 15 minutes. Removable and tiltable 60 L stainless-steel bowl. Bowl-base blade assembly with 2 detachable and height-adjustable fine serrated blades included. 30 to 225 portions (7 oz.) and more.

Select your options at the back page, **F** part.

C TECHNICAL DATA	
Output power	16 HP
Electrical data	208-240V/60/3
Speeds	1800 and 3600 rpm
Dimensions (WxDxH)	29 5/8" × 25 9/16" × 54 1/2" Cube: 36.70
Rate of recyclability	95%
Net weight	443 lbs
Nema #	15-50P
Reference	BLIXER 60 A - 208-240V/60/3

PRODUCT FEATURES / BENEFITS

MOTOR BASE

- Induction direct drive motor for intensive use.
- Power 16 HP.
- 100% stainless-steel construction and three sturdy legs for total stability.
- Stainless steel motor shaft.
- IP65 control panel with flush buttons and digital timer.
- Magnetic safety and motor brake.
- 2 speeds: 1800 and 3600 rpm.
- Pulse function for a better cut precision.

CUTTER FUNCTION

- Removable and tiltable 60 L bowl for effortless emptying and cleaning.
- Bowl-base blade assembly with 2 detachable and height-adjustable blades to ensure a perfectly uniform consistency, even when processing small quantity.
- Stainless-steel construction for making cleaning easier.
- Timer from 0 to 15 minutes for a better preparation control.
- Transparent lid with bowl scraper to improve the end-product consistency and with a lid wiper to enable user to monitor processing.
- Opening in center of lid for adding liquid or dry ingredients during processing.
- 3 retractable wheels making it easier to move the appliance in order to clean the surface.

INCLUDED ACCESSORIES

- 2 stainless steel fine serrated blade assembly
- Scraper arm and lid wiper
- 3 retractable wheels

STANDARDS

ETL electrical and sanitation Listed/ cETL (Canada)



Update: October 2017

Specification sheet

www.robotcoupeusa.com

info@robotcoupeusa.com





Blixer® 60

F OPTIONAL ATTACHMENTS

- Fine serrated edge stainless steel "S" Blade Ref. 57093
- Complete Bowl Assembly Ref. 59148

ELECTRICAL DATA 208-240V/60/3 – delivered with cord and plug.

40 3/8

32

34 1/4