

Countertop Heated Wells

Models: HW-FUL, -43 CHW-FUL, -43

Providing versatility and reliability, Hatco Countertop Heated Wells hold food hot and fresh in either a wet or dry operation with an adjustable temperature control.

The -FUL series can hold a full-size pan or three thirdsize pans, while the -43 series can hold a full-size pan with a third-size pan or four third size pans. The HW-Series are hold only, while the CHW Series are capable of rethermalizing a variety of foods as well as holding (cook and hold).

Standard features

- Controls feature a separate On/Off rocker switch and adjustable temperature dial
- May be used dry but best performance when used with water. Dry indicator lamp informs user to add water
- Thicker .8 mm stainless steel pan with a stainless steel housing (aluminized steel bottom)
- Pan edge offset helps keep condensation from dripping onto countertop surface

Item #	
Quantity	
	(
	HW-FUL with accessory food pans and a pan support bar
CHW-43 with accessory food pans and pan support bars (single unit holding 4 third-size pans)	
Accessories	
Pan Support Bars 12" (305 mm) Pan Support Bar 20" (508 mm) Pan Support Bar	
Rectangular Stainless Steel Food Pans	lf-Size (2 5" [64 mm] H)

□Full-Size (2.5" [64 mm] H) □Full-Size (4" [101 mm] H) □Full-Size (6" [152 mm] H) □ Half-Size (2.5" [64 mm] H) □ Third-Size (2.5" [64 mm] H)

Adapters for HW-FUL and CHW-FUL only Converts unit to hold three 4-Quart (4 Liter) Inserts Converts unit to hold two 7-Quart (7 Liter) Inserts

Adapters for HW-43 and CHW-43 only Converts unit to hold two 11-Quart (10 Liter) Inserts Converts unit to hold four 4-Quart (4 Liter) Inserts

For operation, location and safety information, please refer to the Installation and Operating Manual.




HATCO CORPORATION P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. (414) 671-6350

www.hatcocorp.com | support@hatcocorp.com | Find a Hatco Rep | Image Library | Document Library | Patents | Chat



Countertop Heated Wells

Models: HW-FUL, HW-43, CHW-FUL, CHW-43



Please specify the following with each order:

- 1. Desired Voltage: See chart below
- 2. Models
 - A. HW Holds preheated food only
 - B. CHW Holds and rethermalizes food
- 3. Wattage:
 - A. HW 1200 watts for holding food in wet or dry operation
 - B. CHW 1440 or 1800 watts for rethermalizing food in wet operation OR for holding food in wet or dry operation

4. Agency:


- A. UL and CUL
- B. UL-EPH (sanitary listing)
- C. CE mark available

SPECIFICATIONS Countertop Heated Wells

The shaded areas contain electrical information for International models only

Model	Dimensions (Width x Depth x Height)	Volts	Phase	Watts	Amps	Plug	Cord Location	Approx. Ship Weight
HW-FUL	14.57" x 23.9" x 9.85" (370 x 607 x 250 mm)	120	Single	1200	10.0	NEMA 5-15P	Bottom left corner on back of unit	29 lbs. (13 kg)
		220		1100	5.0	BS-1363		
		230		1200	5.2	BS-1363, CEE 7/7 Schuko, AS-3112, CH1-10P CCC		
HW-43	14.57" x 30.91" x 9.85" (370 x 785 x 250 mm)	120	Single	1200	10.0	NEMA 5-15P		33 lbs. (15 kg)
CHW-FUL	14.57" x 23.9" x 10.83" (370 x 607 x 275 mm)	120		1440	12.0	NEMA 5-15P		29 lbs. (13 kg)
CHW-43	14.57" x 30.91" x 10.83" (370 x 785 x 275 mm)	120		1800	15.0	NEMA 5-15P (US only) NEMA 5-20P (US and Canada only)		35 lbs. (16 kg)

PLUG CONFIGURATIONS



PRODUCT SPECS Countertop Heated Wells

The Countertop Heated Well, manufactured by the Hatco Corporation, Milwaukee, WI 53234 U.S.A.

The Countertop Heated Well shall be rated at ..., rated at ... watts, ... volts, single phase, and be ... inches (millimeters) in overall width. It shall consist of .8 mm thick 304 stainless steel pan, stainless steel housing (aluminized steel bottom) with a metal sheathed heating element, a power On/Off switch, a temperature control, a dry unit indicator light and a 6' (1829 mm) cord with Accessories may include food pans, pan lids, support bars and adapters.

Warranty consists of 24/7 parts and service assistance (U.S. and Canada only).

HATCO CORPORATION P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. (414) 671-6350

www.hatcocorp.com support@hatcocorp.com Find a Hatco Rep Image Library Document Library Patents Chat

plug attached.