



FOOD EQUPIMENT

SERVING THE FOOD INDUSTRY SINCE 1951

66 LBS / 30 KG POTATO PEELER WITH MICROSWITCH AND FLOOR WATER DISCHARGE

Items: 47055 | Model: PP-IT-0030

























FOOD EQUIPMENT POTATO PEELER



TECHNICAL SPECIFICATIONS

Item 47055 Model PP-IT-0030 **Power** 1.2 HP | 0.9 kW **Electrical** 220V / 60Hz / 1 Ph **Capacity** 66.1 lbs | 30 kg **Working Capacity** 700 potatos/hour **Lower Discharge Manifold** ø 1.6" | ø 40 mm **Side Discharge Manifold** ø 2" | ø 50 mm

 Peeling Cycle
 120 - 150 seconds

 Water Temperature
 5 - 20 °C | 41 - 68 °F

RPM 240 RPM


Flexible Pipe Feeding	3/4"	19 mm
Weight	132.3 lbs	60 kg
Gross Weight	149.9 lbs	68 kg


Dimensions 21.7" x 31.5" x 35.4" 550 x 800 x 900 mm

Gross Dimensions 26.4" x 23.2" x 44.1" 670 x 590 x 1120 mm



TECHNICAL DRAWINGS & DIMENSIONS





FEATURES:

- Made from AISI 304 stainless steel, with electric part covered by safety ergonomic plastic case
- · Ventilated asynchronous Italian make motor
- · Belt transmission
- Abrasives designed to enable the user to operate, clean and maintain with the minimum of effort
- Water jets valve
- · Saftey micro-switch working on the cover and chute
- · Water filter drawer for standard and high stand
- · Digital and user-friendly control panel
- · Electrical parts covered by safety ergonomic plastic case
- · Multifunction digital timer
- · Button for manual product discharge
- · Wall or floor discharge outlet

OMCAN INC.

Telephone: 1-800-465-0234 Fax: (905) 607-0234 Email: sales@omcan.com Website: www.omcan.com





Follow us to keep up to date with the latest news and offers











^{*}Refuse bin/drawer not included.

^{*}measurements in diagrams are in mm