



WILSON* WELD-O-GLASS 1850
18-oz Uncoated Fiberglass
Welding Blanket
 Codes: 36290, 36305, 36364, 36144, 36145

Product Information

Code	Material	Description	Size	Qty
36290	6636-1850	18-oz Fiberglass, Uncoated, Grommets, 6 x 6	72" x 72"	1/bag; 10/case
36305	6848-1850	18-oz Fiberglass, Uncoated, Grommets, 6 x 8	72" x 96"	1/bag; 8/case
36364	SP-1850	18-oz Fiberglass, Uncoated, Grommets, 8 x 10	96" x 120"	1/bag; 6/case
36144	1850-40	Roll Goods	40" x 50 yds	1 roll; 50 yds
36145	1850-60	Roll Goods	60: x 50 yds	1 roll; 50 yds

Physical Properties

Color	Tan
Fiberglass	ETG 11.6 (ET9 430 tex) E-Glass filaments
Weight	24.6 oz/yd ² (600 gsm)
Thickness	0.03in (0.75mm)
Strength, Warp (machine direction)	150 lbs/in (2250 N/5cm)
Strength, Fill (cross direction)	135 lbs/in (1216 N/5cm)
Service Temperature	1000F (550c)

WILSON* 18-ounce Uncoated Fiberglass blankets provide basic thermal protection for a variety of uses, such as insulated pads, stress relief welding blankets, welding pads, insulation blankets and lagging. WILSON* 18-ounce Uncoated Fiberglass blankets have a continuous working temperature of up to 1000F. This material provides a good replacement for asbestos welding protection, but should not be used for molten metal protection.



This material is **ANSI FM-4950 approved** for use in vertical applications (1.4.3) with light-moderate exposures resulting from chipping, grinding, heat treating, sand blasting and light horizontal welding; prevents sparks from escaping from a confined area. Certified roll goods feature the ANSI FM imprint every 3' along the edge.

Workmanship Requirement:

Welding Blankets shall be made in accordance with reasonable industry practice with respect to defects or dirt and contamination. Welding Blankets should be packaged as specified in the appropriate quantity as listed.

For additional information: 1-800-255-6401 or KCPInfo@kcc.com

Kimberly-Clark warrants that its products (1) comply with K-C's standard specifications as of the delivery date to K-C's authorized distributors/direct purchasers and are warranted for the following periods from end user's date of purchase (verified by valid sales receipt) (a) five years for Balder Technology auto darkening filters; (b) two years for all other auto darkening filters; and (c) one year for powered air purifying respirators; (2) comply with all K-C labeling representations; and (3) are manufactured in compliance with all applicable federal, state, and local laws in effect at the time and place of manufacture of the products. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. K-C is not liable for any kind of special, incidental, or consequential damages. K-C's liability for breach of contract, tort or other cause of action shall not exceed the product purchase price. Purchasers and users are deemed to have accepted the above warranty and limitation of liability, and cannot change the terms by verbal agreement or by any writing not signed by K-C. To the extent required by applicable law, K-C does not limit its liability for death/injury resulting from K-C's negligence.

