

SAFETY DATA SHEET

1. Identification

Product identifier ANTI-SLIP SAFETY YELLOW AEROSOL SPRAY

Other means of identification

Product code 11930Y

Slip resistant epoxy coating Recommended use

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

NO SKIDDING PRODUCTS, INC. Company name

266 WILDCAT ROAD **Address**

TORONTO, ONTARIO M3J 2N5

Canada

Telephone Information Telephone: (416)667-1788

Website www.noskidding.com E-mail sales@noskidding.com

Emergency phone number Emergency Telephone: (613)996-6666

Supplier Not available.

2. Hazard identification

Flammable aerosols Physical hazards Category 1

> Gases under pressure Classification not possible

Health hazards Acute toxicity, oral Category 4

> Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A Sensitization, skin Category 1 Carcinogenicity Category 2 Reproductive toxicity Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated Category 1

exposure

Aspiration hazard Category 1 Category 2

Hazardous to the aquatic environment, acute

Hazardous to the aquatic environment, Category 3

long-term hazard

Label elements

Environmental hazards



Signal word

Hazard statement Extremely flammable aerosol. Harmful if swallowed. May be fatal if swallowed and enters airways.

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to

aquatic life. Harmful to aquatic life with long lasting effects.

Material name: ANTI-SLIP SAFETY YELLOW AEROSOL SPRAY

SDS CANADA 11930Y Version #: 01 Issue date: 06-09-2022

Precautionary statement

Storage

Prevention Keep out of reach of children. Read label before use. Obtain special instructions before use. Do

not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe gas. Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective

If medical advice is needed, have product container or label at hand. IF SWALLOWED: Response

clothing/eye protection/face protection.

Immediately call a POISON CENTER/doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water, IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical

advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information 47.44% of the mixture consists of component(s) of unknown acute oral toxicity. 61.13% of the

mixture consists of component(s) of unknown acute dermal toxicity. 51.89% of the mixture consists of component(s) of unknown acute inhalation toxicity. 70.64% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 70.64% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

delayed

General information

| Chemical name | Common name and synonyms | CAS number | % |
|-----------------------------|--------------------------|------------|---------|
| Acetone | | 67-64-1 | 27 |
| Toluene | | 108-88-3 | 13.69 |
| XYLENE | | 1330-20-7 | 10.17 |
| Ethylbenzene | | 100-41-4 | 2.48 |
| TITANIUM DIOXIDE | | 13463-67-7 | 1.32 |
| EPOXY RESIN | | 25068-38-6 | 0.5 |
| Other components below repo | ortable levels | | 44.8564 |

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison Inhalation

center or doctor/physician if you feel unwell.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.

Most important symptoms/effects, acute and

Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an

allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Indication of immediate Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim medical attention and special under observation. Symptoms may be delayed.

treatment needed

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

SDS CANADA 11930Y Version #: 01 Issue date: 06-09-2022

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with

Fire fighting

equipment/instructions

Specific methods

face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Containers should be cooled with

water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened

containers. In the event of fire and/or explosion do not breathe fumes.

Extremely flammable aerosol. General fire hazards

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist/vapors. Do not breathe gas. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

| Components | Туре | Value |
|-----------------------|------|---------|
| Acetone (CAS 67-64-1) | STEL | 500 ppm |
| | TWA | 250 ppm |

| US. ACGIH Threshold Limit Value | S | | |
|--|-------------------------------|--------------------|--|
| Components | Туре | Value | |
| Ethylbenzene (CAS 100-41-4) | TWA | 20 ppm | |
| TITANIUM DIOXIDE (CAS 13463-67-7) | TWA | 10 mg/m3 | |
| Toluene (CAS 108-88-3) | TWA | 20 ppm | |
| XYLENE (CAS 1330-20-7) | STEL | 150 ppm | |
| | TWA | 100 ppm | |
| Canada. Alberta OELs (Occupatio | nal Health & Safety Code, Scl | nedule 1, Table 2) | |
| Components | Туре | Value | |
| Acetone (CAS 67-64-1) | STEL | 1800 mg/m3 | |
| | | 750 ppm | |
| | TWA | 1200 mg/m3 | |
| | | 500 ppm | |
| Ethylbenzene (CAS 100-41-4) | STEL | 543 mg/m3 | |

125 ppm 434 mg/m3

100 ppm

10 mg/m3

188 mg/m3 50 ppm

651 mg/m3 150 ppm

434 mg/m3

| | 100 ppm |
|--|---|
| Canada. British Columbia OELs. (Occupational Exposure Li Safety Regulation 296/97, as amended) | mits for Chemical Substances, Occupational Health and |

TWA

TWA

TWA

STEL

TWA

| Components | Туре | Value | Form |
|--------------------------------------|------|----------|----------------------|
| Acetone (CAS 67-64-1) | STEL | 500 ppm | |
| | TWA | 250 ppm | |
| Ethylbenzene (CAS 100-41-4) | TWA | 20 ppm | |
| TITANIUM DIOXIDE (CAS 13463-67-7) | TWA | 3 mg/m3 | Respirable fraction. |
| | | 10 mg/m3 | Total dust. |
| Toluene (CAS 108-88-3) | TWA | 20 ppm | |
| XYLENE (CAS 1330-20-7) | STEL | 150 ppm | |
| | TWA | 100 ppm | |

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value

| Acetone (CAS 67-64-1) | STEL | 500 ppm |
|--------------------------------------|------|----------|
| | TWA | 250 ppm |
| Ethylbenzene (CAS 100-41-4) | TWA | 20 ppm |
| TITANIUM DIOXIDE (CAS 13463-67-7) | TWA | 10 mg/m3 |

SDS CANADA

TITANIUM DIOXIDE (CAS

Toluene (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

13463-67-7)

| Components Toluene (CAS 108-88-3) | Type TWA | 20 ppm |
|--|---|---|
| XYLENE (CAS 1330-20-7) | STEL | 20 ppm 150 ppm |
| ATLENE (CAS 1330-20-1) | TWA | 100 ppm |
| 0 | | |
| Canada. Ontario OELs. (Control of Components | Exposure to Biological or Che Type | mical Agents) Value |
| Acetone (CAS 67-64-1) | STEL | 750 ppm |
| | TWA | 500 ppm |
| Ethylbenzene (CAS 100-41-4) | TWA | 20 ppm |
| FITANIUM DIOXIDE (CAS 13463-67-7) | TWA | 10 mg/m3 |
| Γoluene (CAS 108-88-3) | TWA | 20 ppm |
| (YLENE (CAS 1330-20-7) | STEL | 150 ppm |
| | TWA | 100 ppm |
| anada. Quebec OELs. (Ministry o omponents | f Labor - Regulation respectinզ Туре | g occupational health and safety) Value Form |
| Acetone (CAS 67-64-1) | STEL | 2380 mg/m3 |
| , | | 1000 ppm |
| | TWA | 1190 mg/m3 |
| | | 500 ppm |
| thylbenzene (CAS 00-41-4) | STEL | 543 mg/m3 |
| | | 125 ppm |
| | TWA | 434 mg/m3 |
| | | 100 ppm |
| ITANIUM DIOXIDE (CAS 3463-67-7) | TWA | 10 mg/m3 Total dust. |
| oluene (CAS 108-88-3) | TWA | 188 mg/m3 |
| | | 50 ppm |
| (YLENE (CAS 1330-20-7) | STEL | 651 mg/m3 |
| | | 150 ppm |
| | TWA | 434 mg/m3 |
| | | 100 ppm |
| anada. Saskatchewan OELs (Occ components | cupational Health and Safety Re Type | egulations, 1996, Table 21) Value |
| Acetone (CAS 67-64-1) | 15 minute | 750 ppm |
| | 8 hour | 500 ppm |
| Ethylbenzene (CAS | 15 minute | 125 ppm |
| | | |
| 00-41-4) | 8 hour | 100 ppm |
| 100-41-4) TITANIUM DIOXIDE (CAS | 15 minute | 20 mg/m3 |
| 100-41-4) TITANIUM DIOXIDE (CAS 13463-67-7) | 15 minute 8 hour | 20 mg/m3 10 mg/m3 |
| TITANIUM DIOXIDE (CAS 13463-67-7) Toluene (CAS 108-88-3) | 15 minute 8 hour 15 minute | 20 mg/m3 10 mg/m3 60 ppm |
| 100-41-4) TITANIUM DIOXIDE (CAS 13463-67-7) | 15 minute 8 hour | 20 mg/m3 10 mg/m3 |

SDS CANADA

11930Y Version #: 01 Issue date: 06-09-2022

Biological limit values

| ACGIH | Biologica | I Exposure | Indices |
|--------------|-----------|------------|----------|
| | Diviogica | LAPOSUIE | IIIUICES |

| Components | Value | Determinant | Specimen | Sampling Time |
|-----------------------------|-----------|---|---------------------|---------------|
| Acetone (CAS 67-64-1) | 25 mg/l | Acetone | Urine | * |
| Ethylbenzene (CAS 100-41-4) | 0.15 g/g | Sum of mandelic acid and phenylglyoxylic acid | Creatinine in urine | * |
| Toluene (CAS 108-88-3) | 0.3 mg/g | o-Cresol, with hydrolysis | Creatinine in urine | * |
| | 0.03 mg/l | Toluene | Urine | * |
| | 0.02 mg/l | Toluene | Blood | * |
| XYLENE (CAS 1330-20-7) | 1.5 g/g | Methylhippuric acids | Creatinine in urine | * |

^{* -} For sampling details, please see the source document.

Exposure guidelines

Canada - Alberta OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Toluene (CAS 108-88-3) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Applicable for industrial settings only. Chemical respirator with organic vapor cartridge and full

facepiece.

Skin protection

Hand protection Applicable for industrial settings only. Wear appropriate chemical resistant gloves.

Other Applicable for industrial settings only. Wear appropriate chemical resistant clothing. Use of an

impervious apron is recommended.

Respiratory protection Applicable for industrial settings only. Chemical respirator with organic vapor cartridge and full

facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid, Gas. Aerosol. **Form** Color Yellow Odor Solvent. **Odor threshold** Not available. Ηq Not available. Melting point/freezing point Not available. Not available. Initial boiling point and boiling range

Flash point -133.6 °F (-92.0 °C)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable. Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

1.3 % estimated

(%)

Flammability limit - upper

12.8 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 1708.72 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density6.50 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.Percent volatile78.49 %w/w

Specific gravity 0.78

VOC 546.81 g/l COATING 401.31 g/l MATERIAL

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong acids. Strong oxidizing agents. Chlorine. Fluorine. Halogens. Nitrates.

Hazardous decompositionNo hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or

vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an

allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components **Species Test Results**

Acetone (CAS 67-64-1)

Acute

Dermal

LD50 Guinea pig, rabbit, rat 7400 mg/kg

Inhalation

LD50 Rat 7600 mg/m3, 4 hours

Oral

LD50 Rat 5800 mg/kg

TITANIUM DIOXIDE (CAS 13463-67-7)

Acute Inhalation

LC50 > 6.82 mg/kg

Oral

LD50 > 5000 mg/kg

Toluene (CAS 108-88-3)

Acute Dermal

LD50 5000 mg/kg

Inhalation

LC50 Rat 20 mg/l

Oral

LD50 5000 mg/kg

XYLENE (CAS 1330-20-7)

Acute

Dermal

LD50 12130 mg/kg

Inhalation

LC50 27120 mg/m3

Oral

LD50 3523 mg/kg

Skin corrosion/irritation Causes skin irritation. Causes serious eye irritation.

Serious eye damage/eye irritation

Respiratory or skin sensitization Canada - Alberta OELs: Irritant

> Irritant TITANIUM DIOXIDE (CAS 13463-67-7)

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Suspected of causing cancer. Carcinogenicity

ACGIH Carcinogens

Acetone (CAS 67-64-1) A4 Not classifiable as a human carcinogen.

Ethylbenzene (CAS 100-41-4) A3 Confirmed animal carcinogen with unknown relevance to

humans.

TITANIUM DIOXIDE (CAS 13463-67-7) A4 Not classifiable as a human carcinogen. Toluene (CAS 108-88-3) A4 Not classifiable as a human carcinogen. XYLENE (CAS 1330-20-7) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Acetone (CAS 67-64-1) Not classifiable as a human carcinogen.

Ethylbenzene (CAS 100-41-4) Confirmed animal carcinogen with unknown relevance to humans.

Not classifiable as a human carcinogen.

TITANIUM DIOXIDE (CAS 13463-67-7)

Toluene (CAS 108-88-3) Not classifiable as a human carcinogen. XYLENE (CAS 1330-20-7) Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylbenzene (CAS 100-41-4) 2B Possibly carcinogenic to humans. TITANIUM DIOXIDE (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans. XYLENE (CAS 1330-20-7) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in

laboratory animals. Suspected of damaging fertility or the unborn child.

Specific target organ toxicity single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated **Chronic effects**

exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

| Components | | Species | Test Results |
|----------------------|-----------------|--------------------------------------|------------------------------|
| Acetone (CAS 67-64-1 |) | | |
| Aquatic | | | |
| Crustacea | NOEC | Freshwater invertebrate | > 79 mg/l |
| Fish | LC50 | Freshwater fish | 5540 mg/l |
| Ethylbenzene (CAS 10 | 00-41-4) | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 1.37 - 4.4 mg/l, 48 hours |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | 7.711 - 9.591 mg/l, 96 hours |
| | | Fathead minnow (Pimephales promelas) | 11.5 - 12.7 mg/l, 96 hours |
| TITANIUM DIOXIDE (| CAS 13463-67-7) | | |
| Other | EC50 | Pseudokirchnerella subcapitata | > 100 mg/l |
| | NOEC | Pseudokirchnerella subcapitata | >= 100 mg/l |
| Aquatic | | | |
| Algae | EC50 | Marine water algae | > 10000 mg/l |
| | NOEC | Marine water algae | 5600 mg/l |
| Crustacea | EC50 | Daphnia magna | > 100 mg/l |
| | LC50 | Marine water invertebrate | > 10000 mg/l |
| | NOEC | Daphnia magna | > 1 mg/l |
| Fish | LC50 | Freshwater fish | > 100 mg/l |
| | | Marine water fish | > 10000 mg/l |
| | NOEC | Freshwater fish | > 500 mg/l |
| Toluene (CAS 108-88- | 3) | | |
| Aquatic | | | |
| Algae | LC50 | Freshwater algae | 134 mg/l |
| | NOEC | Freshwater algae | 10 mg/l |
| Crustacea | LC50 | Water flea (Ceriodaphnia dubia) | 3.78 mg/l, 48 hours |
| | NOEC | Water flea (Ceriodaphnia dubia) | 0.74 mg/l |
| Fish | LC50 | Freshwater fish | 5.5 mg/l |
| | NOEC | Freshwater fish | 1.4 mg/l |
| | | | |

Material name: ANTI-SLIP SAFETY YELLOW AEROSOL SPRAY

SDS CANADA 11930Y Version #: 01 Issue date: 06-09-2022

Components **Species Test Results** XYLENE (CAS 1330-20-7) **Aquatic** Algae EC50 Freshwater algae 1.3 mg/l NOEC Freshwater algae 0.44 mg/l EC50 Crustacea Freshwater invertebrate 1 mg/l **NOEC** Freshwater invertebrate 0.96 mg/l Fish LC50 Bluegill (Lepomis macrochirus) 10.464 - 13.762 mg/l, 96 hours Freshwater fish 2.6 mg/l

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

 Acetone
 -0.24

 Ethylbenzene
 3.15

 Toluene
 2.73

 XYLENE
 3.12 - 3.2

NOEC

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

Freshwater fish

potential.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

> 1.3 mg/l

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

TDG

UN number UN1950

UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not available.
Environmental hazards Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number ID8000

UN proper shipping name Consumer commodity, Limited Quantity

Transport hazard class(es)

Class 9
Subsidiary risk ORM-D
Packing group Not available.

Environmental hazards No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

aliciali

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950

UN proper shipping name Aerosols, flammable, Limited Quantity

Not established.

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not available.

Environmental hazards

Marine pollutant No.

EmS Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.


Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

IATA



IMDG; TDG



15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada. Excluded VOCs. Guidelines for Volatile Organic Compounds in Consumer Products. CEPA 1999. Environment Canada, as amended

Acetone (CAS 67-64-1)

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

Acetone (CAS 67-64-1)

Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

Precursor Control Regulations

Acetone (CAS 67-64-1) Class B

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

Country(s) or region

International Inventories

| Australia | Australian Inventory of Chemical Substances (AICS) | No |
|-------------|--|----|
| Canada | Domestic Substances List (DSL) | No |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | No |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | No |
| New Zealand | New Zealand Inventory | No |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |

Taiwan Taiwan Chemical Substance Inventory (TCSI) No United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory No

16. Other information

06-09-2022 Issue date

Version # 01

Disclaimer The information and recommendations in this safety data sheet are, to the best of our knowledge,

accurate as of the date of issue. Nothing herein shall be deemed to create any warranty, expressed or implied. It is the responsibility of the user to determine the applicability of this

information and the suitability of the material or product for any particular purpose.

Product and Company Identification: Product Uses **Revision information**

Inventory name

Physical & Chemical Properties: Multiple Properties

Regulatory Information: United States

GHS: Classification

11930Y Version #: 01 Issue date: 06-09-2022

On inventory (yes/no)*

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).