

## TECHNICAL DATA SHEET

### SLIP RESISTANT TEXTURED AEROSOL EPOXY SPRAY #11930 SERIES

#### DESCRIPTION

- Cures to a hard slip resistant textured finish
- Adheres to fiberglass, wood, steel, concrete and other surfaces where a slip resistant finish is desired
- Effective on steps, ramps, loading docks, fire escape ladders, stair treads, pool surroundings, boat decks and around machinery
- Self priming on most surfaces
- Quick drying. For use indoors and outdoors
- Available in clear, white, black, grey and safety yellow

**Please note: Clear Epoxy color has a slight amber hue to it and should not be used on white surface. Use 11935C if crystal clear results is required. Use 11935W Acrylic Anti Slip Aerosol if a whiter white is desired relative to 11930W Epoxy Anti Slip Aerosol.**

#### PRODUCT CHARACTERISTICS

A slip resistant epoxy coating that cures to a tough, textured finish. Designed for exterior and interior use on concrete, steel, wood, fiberglass, aluminum, tile, etc. Particularly effective anywhere water or other slippery conditions exist. Contains synthetic grit with no sharp edges.

- Adheres to most hard surfaces
- A cost-effective method of coating small areas
- Easy to apply, sets up quickly
- Contains micro traction grit.

#### TECHNICAL DATA

Resin Type	Epoxy Ester
Lbs / Gal	6.84 #/Gal.
Solid Weight	23 – 26%
Solid Volume	12 – 14%
Dry to Touch	10 – 20 minutes at 77°F
Dry hard	24 hours at 77°F

Clean Up – Thinner, Toluene, Xylene, or Lacquer Thinner

Product Specifications	
Type	Slip resistant textured epoxy coating, Spray Product# 11930 Series
Coverage	Approximately 20sq. ft.
Appearance/Odor	Viscous Liquid / Strong solvent odor
Flash Point of Concentrate	45°F
Aerosol Flammability	Extremely Flammable Spray
Specific Gravity of Concentrate	0.800
Propellant	Liquefied Petroleum
Spray Pattern	Circular Coarse Fan Spray
NFPA Fire Rating	Level 3 Aerosol

**NOTICE: READ AND FULLY UNDERSTAND SDS BEFORE USING. This product is designed to help reduce the hazards of slippery areas. This product cannot eliminate slipping.**

**IMPORTANT NOTICE:** Seller and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended purpose, and the user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer. Buyer assumes all risks and liability associated with disposal.

E & O.E.

April 22, 2014