

TECHNICAL DATA SHEET

NO SKIDDING[®] SLIP RESISTANT FLOOR CLEANER / MAINTAINER S.R.C. No. 71378

DESCRIPTION

REDUCES POTENTIAL FOR SLIPS AND FALLS AND INCREASES SLIP RESISTANCE.

No Skidding[®] Slip Resistant Floor Cleaner/Maintainer S.R.C. is designed to increase the slip resistance of sealed concrete, epoxy and painted, glazed quarry & ceramic tile, brick, rubber, terrazzo and similar surfaces. Cleans and treats the floor with slip reducing ingredients that increases the slip resistance and the potential for slip and falls. Effective one step cleaning with no final rinsing.

Suitable for manufacturing facilities, warehouses, food processing plants, loading docks, shopping malls, restaurants, offices, schools, etc.

- UL Listed for slip resistance for dry (COF)
- ANSI A137.1 for slip resistance for wet (DCOF)

FEATURES AND BENEFITS

- Increases Slip-Resistance
- Detergent and Concentrated
- Thin Invisible Film
- Foam Control
- Polymer Base
- Reduces Potential for Slip and Fall Accidents
- Economical to Use
- Does not clog recovery tank on automatic scrubbers

TECHNICAL DATA

PROPERTY	VALUES
pH	11.0 – 11.5
Specific Gravity	1.01
Viscosity	Water Thin
Melting point/freezing point	No information available
Flash Point	Above 200°F
Boiling point/boiling range	No information available
Evaporation rate	Same as water
Flammability (solid,gas)	
Flammability Limits in Air	
Upper flammability limit	No information available
Lower flammability limit	No information available
Vapor pressure	No information available
Vapor density	No information available
Water solubility	Soluble in water
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Density Lbs/Gal	8.39
VOC Content (%)	5.78% VOC CARB COMPLIANT for product category

SURFACE PREPARATION

- It is important to first get your floors under control for optimal safety. Use this procedure to address any sealed, glazed, painted, epoxy coated floor surface that is a candidate for slip & fall improvement. We suggest using a two-bucket or split bucket system which provides a separate bucket for diluted S.R.C. solution and a second bucket for clean rinse water. Utilizing color-coded mops to include microfiber mops, helps to keep things separate with clean solution in one bucket and soiled solutions in the other. If used correctly, your rinse water should be changed three times before the cleaner.
1. Dust mop floor surface using clean, untreated dust mop or microfiber dust mop.
 2. Using the two or split bucket system, prepare a two-gallon solution of S.R.C. at 8-10 oz. per gallon of warm water in the first bucket. Pour two gallons of clean water for rinse in the second bucket.
 3. Spread solution to floor surface and spread evenly allowing sufficient contact time.
 4. Scrub with deck brush, floor machine or auto scrubber with appropriate pad/brush.
 5. Recover slurry / residue by using a wet / dry vacuum for best results.
 6. Reapply uncontaminated S.R.C. from the first bucket to the pre-cleaned floor with a tightly wrung mop or microfiber mop. Let dry, no rinsing required.
 7. Allow entire floor surface to air dry using a portable floor dryer to speed up drying process. Allow floor surface to dry completely.
 8. An auto scrubber can be used for this application. Dilute S.R.C. at 12 oz. per gallon of warm water in the solution tank. Using the double pass system, lay solution down and scrub at the same time. Then proceed to vacuum up solution. Repeat steps 6-7 above to the now clean floor area.

APPLICATION METHOD FOR FLOORS

Daily Slip Treatment and Cleaning Procedures.

Damp Mopping: No-rinse procedure for light soils.

1. Dilute S.R.C. at 2-4 oz. per gallon of warm water if available.
2. Damp mop area to be cleaned and treated.
3. Reload mop / microfiber mop with fresh solution and continue applying to entire floor surface.
4. Allow floor surface to air dry or the use of a portable floor dryer can be used to speed up drying process. Very important for floor surface to dry completely.

Auto Scrubber: Use Appropriate Pads / Brushes

1. Dilute S.R.C. at 2 oz. per gallon of warm water if available in solution tank. For heavy soils dilute at 4 oz. per gallon of water. Use the double pass system laying down solution and scrubbing at the same time. Then proceed to vacuum up solution.
2. Allow floor surface to air dry or the use of a portable floor dryer can be used to speed up drying process. Very important for floor surface to dry completely.

SAFETY INFORMATION

Precautionary Statements – Prevention

Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements – First Aid Measures

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Drink plenty of water.

IMPORTANT NOTICE: This product cannot eliminate slipping. Seller and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended purpose, and the user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer. Buyer assumes all risks and liability associated with disposal. E. & O.E.