



## Multi-Star Modular Downlights

SKU: SL-MSM12WTC (Tri-colour 3000k, 4000k, 5000k)

SKU: SL-MSM12W3k (CREE X LAMP CRI93)

SKU: SL-MSM12W4k (CREE X LAMP CRI93)



DIMMING



IP20



IK04



warranty

3 Years



3000k



4000k



5000k

Tri-Colour / CREE X Lamp



Multi-Star is a modular spot downlight system.

Precise directional lighting is achieved by the many choices of fittings, reflectors and lenses.

The choices of module include a standard tri-colour module or a high end CREE CRI93 Module.

Beam angles from narrow to wide can be selected with several optic reflectors & low glare lenses.

<b>Voltage</b>	240VAC
<b>Power</b>	12 watt
<b>Emitting Colour</b>	Warm white, Natural white, Daylight
<b>Kelvin (CRI)</b>	3000k, 4000k, 5000k
<b>Lumens/watt</b>	86.6 (ww) 93.3 (nw) 100 (dl)
<b>Delivered lumens</b>	1040 (ww) 1120 (nw) 1200 (dl)
<b>Dimensions</b>	Adjustable x H70mm
<b>Colour rendering</b>	>83 (tri-color), >93 (CREE X-Lamp)
<b>IP rating</b>	IP20
<b>Dimming</b>	Yes
<b>Beam angle</b>	15°, 28°, 40°, 60° - reflector 24°, 36°, 60° - UGR19 lens
<b>Fitting colour</b>	White / Black
<b>Warranty</b>	3 years

# MultiStar - Choose your options



**D = Diameter**      **H = Height**  
**C/O = Cut out**      **W = Width**



## REFLECTOR OPTIONS



The 8643 frames come standard with honeycomb for a low glare effect when the light is on & a more attractive appearance when the light is off. There are 4 reflectors to choose from.

### D86 x H43 Fixed - 75mm C/O

Lens angle      24°, 36°, 60°  
 Beam angle      15°, 28°, 40°, 60°  
**SKU: 8643**



### D80 x H42 Adjustable small round—70mm C/O

Lens angle      24°, 36°, 60°  
 Beam angle      15°, 28°, 40°, 60°  
**SKU: 8042**



### D100 x H25 Adjustable round - 90mm C/O

Lens angle      24°, 36°, 60°  
 Beam angle      15°, 28°, 40°, 60°  
**SKU: 1025**



### W100 x 100 x H25mm Adjustable Square - 90 x 90 C/O

Lens angle      24°, 36°, 60°  
 Beam angle      15°, 28°, 40°, 60°  
**SKU: 1010**



### W185 x 100 x H25mm Adjustable Square - 160 x 90 C/O

Lens angle      24°, 36°, 60°  
 Beam angle      15°, 28°, 40°, 60°  
**SKU: 1810**



### W270 x 100 x H25mm Adjustable Square - 255 x 90 C/O

Lens angle      24°, 36°, 60°  
 Beam angle      15°, 28°, 40°, 60°  
**SKU: 2710**