Model:

Traditional Reach-In's:

S-47R

Reach-In Solid Swing Door Refrigerator





S-47R

- Stainless steel interior and exterior retains attractive finish longer.
- Rounded corner design inside of the cabinet makes it easy to clean the inside storage room
- Standard door features:
 Heavy-duty pull handle
 Each door with two spring hinges, this make the door self-closing with with enduring quality
- R290 Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) for the best in food preservation.
- Electronic control system:
 Adjustable temperature set point and defrost frequency
 Error codes to diagnose service issues
- Shelf: Adjustable, heavy duty PVC coated shelves.
- Standard heavy-duty casters make it easy to move and clean underneath

Bottom mounted units feature:

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

| | | | Cabinet Dimensions (inches) (mm) | | | CAP. CU.FT. | | | | |
|-------|-------|---------|--|---------------|----------------|----------------|------|----------|------|--------------|
| Model | Doors | Shelves | L | D | Н | LITER | ΗP | Voltage | Amps | NEMA Config. |
| S-47R | 2 | 6 | 54 1371 | 32-1/4 818 | 82-1/2 2095 | 47 1321 | 1/2+ | 115/60/1 | 4.56 | 5-15P |

Plug type varies by country.





与へ目へ

S-47R Plan View



