Model:

Traditional Reach-In's:

S-72F

Reach-In Solid Swing Door Freezer





S-72F

- Stainless steel interior and exterior retains attractive finish longer.
- Rounded corner design inside of the cabinet makes it easy to clean the inside storage room
- Standard door features: Heavy-duty pull handle Each door with two spring hinges, this make the door self-closing with with enduring quality
- R290 Refrigeration system holds
 -8°F to 0°F (-22°C to -18°C) for the best in food preservation.
- Electronic control system:
 Adjustable temperature set point and defrost frequency
 Error codes to diagnose service issues
- Shelf: Adjustable, heavy duty PVC coated shelves.
- Standard heavy-duty casters make it easy to move and clean underneath

Bottom mounted units feature:

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

			Cabinet Dimensions (inches) (mm)			CAP.				
Model	Doors	Shelves	L	D	Н	CU.FT. LITER	HP	Voltage	Amps	NEMA Config.
S-72F	3	9	80-7/8 2054	32-1/4 818	82-1/2 2095	72 2040	1	115/60/1	13.32	5-20P

Plug type varies by country.







S-72F Plan View

